



HUMBLE OIL & REFINING COMPANY - EXXON

-----DRINKARD COMPLETION: August 1999 -----

WELL: HSOG #1
SURFACE LOCATION: UL "I" Sec 22 - 22S - 37E (NE/4 SE/4)
(2194' FSL & 479' FEL of Section 22)

Orig Spud Date: 12/31/48
TD: 7940'
Rig Rel: 3/12/49
Elev Csg: 3348'
Elev GL: 3340'

COUNTY, STATE: Lea County, NM
FIELD: Drinkard (19190)

First Production: 3/12/49
API No. 30-25-10402

Hole Size

15" Hole

Surface Csg:
10-3/4" 40# H-40 @ 322' cmt'd to surface
w/ 275 sx cmt

Home-Stake Re-entry: 08/21/99
Ready to produce: 10/25/99

9-7/8" Hole

Intermediate Csg:
7-5/8" 26.4# J-55 @2780' cmt'd to surface
w/ 1500 sx cmt

Tubing: 194 jts 2-7/8" tbg
T/A 2-7/8" x 5-1/2"
10 jts 2-7/8" tubing
S/N
M/A 2-7/8" x 20'

Rods: Pol Rod 1-1/2" x 20'
64 7/8" rods
183 3/4" rods
12 7/8" rods
Pump: 2-1/2" x 1-1/4" x 20' w/ 6' gas anchor

6-3/4" Hole

Old Blinebry
Sqz'd 9/1/99
w/ 150 sx

Perfs: 5435-65', 5485-5505', 5535-60'
Perfs: 5575-5645', 5665-90'

Jan '55: Re-entered plugged
Ellenberger well & completed in
Blinebry. Blinebry produced until
P&A'd June 1980.

Sept '77: Attempted Drinkard
recompletion - would not
produce. Set plug in nipple @
6057', opened sldg sleeve @
5957' & returned to Blinebry.

Old Drinkard
sqz'd w/ 200 sx
New Drinkard

Perfs: 6192-98', 6205-07', 6218-26', 6232-84'
Perfs: 6326', 36', 38', 44', 51', 62', 66', 68', 72', 78', 80', 86', 98'
6400', -03', -27', -53', -63', -82', -86'

PBTD - 6555'
Ellenberger (O/H)

TD 7940'

Production Csg:
5-1/2" 14#, 15.5#, 17# K-55 @7883' 1st Stage: 100 sx cmt
2nd Stage: 675 sx cmt

Cmt plugs drilled out to 6555'

