

OIL CONSERVATION COMMISSION
 Santa Fe, New Mexico
MISCELLANEOUS REPORTS ON WELLS

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO
 RECEIVED
 MAY 2 - 1949

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission. Indicate nature of report by checking below.

| | |
|--|---|
| REPORT ON BEGINNING DRILLING OPERATIONS | REPORT ON REPAIRING WELL |
| REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL | REPORT ON PULLING OR OTHERWISE ALTERING CASING |
| REPORT ON RESULT OF TEST OF CASING SHUT-OFF | REPORT ON DEEPENING WELL |
| REPORT ON RESULT OF PLUGGING OF WELL | REPORT OF SETTING CASING X |

April 27, 1949 Midland, Texas
 Date Place

OIL CONSERVATION COMMISSION,
 SANTA FE, NEW MEXICO
 Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Rowan Oil Company Will Cary Well No. 6 in the _____
 Company or Operator Lease
NE of NW of Sec. 22, T. 22N, R. 37E, N. M. P. M.,
Cary Field, Lea County.

The dates of this work were as follows: April 19, 1949
 Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on April 18 1949
 and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We have run 232 jts, 7082' 5 1/2" 17# J-55 casing, set at 7095' with 80 sacks common cement. After cement had set 24 hrs, ran temperature survey, found top of cement at 6275'. Perforated casing with four 1/2" shots at 6270', cemented with 500 sacks common cement. Squeezed 50 sacks in formation through perforations at 6270'. After cement was allowed to set 36 hrs, ran temperature survey, found top of cement at 2750'. Cement was then drilled out of casing. Casing tested with 1900#. Test o.k. Float and shoe were drilled. Casing tested with 1900#. Test o.k.

Witnessed by L. N. Addison Rowan Oil Company Division Production Supt.
 Name Company Title

Subscribed and sworn before me this _____
27th day of April 1949
Clyde D. McHam
 Notary Public
 My commission expires JUN 1 1949

I hereby swear or affirm that the information given above is true and correct.
 Name L. N. Addison
 Position Division Production Superintendent
 Representing Rowan Oil Company
 Company or Operator
 Address Box 1873, Midland, Texas

Remarks:

APPROVED

MAY 3 1949

Ray G. ...
 Title

Wissenschaftliche Arbeit

Titel: ...

Main body of the document containing several paragraphs of text, possibly a list of items or a detailed report. The text is very faint and difficult to read.

Handwritten signature or name at the bottom left of the page.