

NEW MEXICO OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

MISCELLANEOUS NOTICES

HOBBS OFFICE

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	XX
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

November 18, 1949

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the

Skelly Oil Company

J. V. Baker

Well No. 9 in SE 1/4 SW 1/4

Company or Operator

Lease

of Sec. 22, T. 22S, R. 37E, N. M. P. M., Cary Field.

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

Well drilled to total depth of 7362'. On DST taken in Montoya section, recovered 2850' of sulphur water. No oil or gas in commercial quantities encountered through any section - Dry Hole - Will be plugged and abandoned in accordance with rules and regulations of the New Mexico Oil Conservation Commission as follows.

Will run cement plug of 50 sacks 7362' to 7118' then fill with heavy mud laden fluid to 6300'. Will run cement plug of 50 sacks 6300' to 6137' then fill with heavy mud laden fluid to 5030'. Will run cement plug of 30 sacks 5030' to 4932' then fill with heavy mud laden fluid to 3700'. Will run cement plug of 50 sacks 3700' to 3537' then fill with heavy mud laden fluid to 2800'. Will run cement plug of 20 sacks 2800' to 2738' (8-5/8" casing set at 2790' and cemented to surface) Will fill with heavy mud laden fluid 2738' to 47'. Will then run cement cap of 15 sacks, and install 4" pipe marker.

Confirming oral approval given by Mr. Roy Yarbrough to J. N. Dunlavy.

Approved _____, 19____
except as follows:

Skelly Oil Company

Company or Operator

By

Position

Dist. Supt.

Send communications regarding well to

Name

Skelly Oil Company

Address

Drawer "D"

Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

