

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<b>XX</b>		

Nov. 20, 1949

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_  
**Skelly Oil Company** **J. V. Baker** Well No. **9** in the \_\_\_\_\_

SE/4 SW/4 Company or Operator **22** Lease **225** of Sec. **22**, T. **22S**, R. **37E**, N. M. P. M.,  
**Cary** Field, **Lee** County.

The dates of this work were as follows: **November 18, 1949**

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on **Nov. 18,** 19**49**  
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED  
Drilled to T.D. 7362', no oil or gas encountered in commercial quantities - Dry Hole -  
Was plugged in following manner:

Ran 75 sacks cement 7362-7118'; heavy mud laden fluid 7118-6300'; 50 sacks cement 6300-6137'; heavy mud laden fluid 6137-5030'; 30 sacks cement 5030-4932'; heavy mud laden fluid 4932-3700'; 50 sacks cement 3700-3537'; heavy mud laden fluid 3537-2800'; 20 sacks cement 2800-2738'; heavy mud laden fluid 2738-47'. Then ran cement cap of 15 sacks filling to surface. Installed 4" pipe marker. (8-5/8" casing set and cemented at 2790 was left in hole)

Witnessed by <b>I. W. Rogers</b>	<b>Makin Drilling Co.</b>	<b>Tool Pusher</b>
Name	Company	Title
Subscribed and sworn before me this <b>21-st</b> day of <b>November</b> 19 <b>49</b>		
<b>W. R. Lusk</b> Notary Public		
I hereby swear or affirm that the information given above is true and correct. Name <b>W. R. Lusk</b> Position <b>District Superintendent</b> Representing <b>Skelly Oil Company</b> Company or Operator Address <b>Drawer "D" - Hobbs, New Mexico</b>		
MY COMMISSION EXPIRES AUG. 19, 1952 My commission expires _____		

Remarks:

**Ray J. P. Lusk**  
Name  
Title