

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

SEP 21 1949

**DUPLICATE**

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, N.M.

Sept. 19, 1949

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

Skelly Oil Co.

J. V. Baker

Well No. 9

in SE/4 SW/4

Company or Operator

37E

Lease

Lea

County.

of Sec. 22

T

R

N. M. P. M.

Field.

South

2086

The well is 766 feet (N.) (S.) of the line and 2086 feet (E.) (W.) of the West line of Sec. 22

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is

J. V. Baker

Eunice, New Mexico

Address

If government land the permittee is

Address

Skelly Oil Co.

The lessee is

Tulsa, Okla.

Address

We propose to drill well with drilling equipment as follows:

LOCATE WELL CORRECTLY

Rotary tools from surface to total depth

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
17"	13-3/8	40.5	New	220	Cemented	250
11"	8-5/8	28	"	2700	"	1200
7-7/8"	5-1/2"	17	"	7300	"	600

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 7300 feet.

Additional information:

Halliburton process shall be used on all cement jobs and cement circulated back to surface on 13-3/8".

Approved SEP 1 1949, 19  
except as follows:

Sincerely yours,

Skelly Oil Company

Company or Operator

By

Dist. Supt.

Position

Send communications regarding well to

Name Skelly Oil Co.

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Title

OIL &amp; GAS INSPECTOR