

CONSERVATION COMMISSION
Santa Fe, New Mexico
MISCELLANEOUS REPORTS ON WELLS

RECEIVED
AUG 14 1947
HOBBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Jetting Casing	X

August 11, 1947

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____

Amerada Petroleum Corporation **Eugene Wood** Well No. **5** in the _____

Company or Operator _____ Lease _____
NW 1/4 NE 1/4 of Sec. **22**, T. **22S**, R. **37E**, N. M. P. M.,
Hudson Field, **Lea** County.

The dates of this work were as follows: August 11, 1947

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on August 10, 19 47
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

2750' Total Depth, Line. Ran 3 joints of 8-5/8" OD, 32#, G-C, R-2, 10-V-Thd., SS Casing Second Hand, 33 joints of 8-5/8" OD, 32#, J-55, R-3, 8-RT, Long T/C, Spang SS Casing New and 44 joints of 8-5/8" OD, 32#, J-55, R-2, 8-RT, Reg.T/C Spang SS Casing New and set at 2747'. Cemented with 1000 sacks of El Toro 3% Howsogel Cement, 500 sacks of El Toro Regular Cement and 50 sacks of Incor Cement and plug pumped to 2691' at 11:00AM with 900#. Cement circulated. Spot welded first five collars.

Witnessed by D. W. Gordon Amerada Petroleum Corporation Fern Boss
Name Company Title

Subscribed and sworn before me this _____ I hereby swear or affirm that the information given above is true and correct.

11th day of August, 19 47 Name [Signature]

Position Asst. Dist. Supt.

Representing Amerada Petroleum Corporation
Company or Operator

My commission expires _____ By Commission Expires May 9, 1948 Address Drawer D, Monument, New Mexico

Remarks:

AUG 14 1947

[Signature]
Name
Oil & Gas Inspector
Title