


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	9-5/8"	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Hobbs, N.M.
PlaceApril 24, 1946
DateOIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation O.I. Boyd Well No. 3 in the
Company or Operator LeaseC. NE SW of Sec. 23, T. 22 S, R. 37 E, N. M. P. M.,
Drinkard Field, Lea County.

The dates of this work were as follows: Cemented April 21; tested April 23, 1946

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on April 22 1946
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Temperature survey showed cement behind 9-5/8" casing at 750' below rotary table. The hole was washed down and the casing tested with 1200# pressure applied for 30 minutes. The plug was drilled and the hole tested with 1200# pressure applied for 30 minutes. Both tests were OK, and after approval of Mr. Yarbrough, State Oil and Gas Inspector, preparations were made to drill ahead.

Witnessed by H. L. Campbell Name Gulf Oil Corporation Company Rotary Foreman Title

Subscribed and sworn before me this

24th day of April, 1946

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name E. J. Gallagher

Position District Sup't.

Representing Gulf Oil Corporation
Company or Operator

My commission expires 2-23-50

Address Hobbs, N.M.

Remarks:

APPROVED

Date APR 27 1946

Name
Inspector
Title



LTR



Job separation sheet

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	9-5/8"	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, N.M.
PlaceApril 22, 1946
Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the _____

Gulf Oil Corporation O. J. Boyd Well No. 3 in C. NE SW
Company or Operator Lease
of Sec. 23, T. 22 S, R. 37 E, N. M. P. M., Drinkard Field
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

On April 21, 1946, the 9-5/8" OD 8 Rnd Thd 36# Pittsburgh Seamless Steel Grade H-40 new casing was set in Anhydrite at 2863' and cemented by Halliburton Oil Well Cementing Company with 1200 sacks 2% Aquagel and 100 sacks neat cement. The plug was pumped to 2829'. The job was started at 2.00 PM and completed at 8.00 PM.

Propose to drill plug and test shut off at 3.00 PM April 23, 1946.

Approved APR 27 1946, 19____
except as follows:

OIL CONSERVATION COMMISSION,
By Roy Warkrough
Title Oil & Gas Inspector

Gulf Oil Corporation
Company or Operator
By E. J. Gallagher
Position District Sup't.
Send communications regarding well to
Name E. J. Gallagher
Address P.O. Box 1687
Hobbs, N.M.