State of New Mexico Energy, Minerals and Natural Resources Department

Form C·103

Revised 1-1-89

| DISTRICTIII DISTRICTIII SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PHONOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVORL USE "APPLICATION FOR PERMIT" (FORM C. 101) FOR SUCH PROPOSALS.) 1. Type of Well: ORDER C. 11 3. Addirex of Operator John H. Hendrix Corporation John H. Hendrix Corporation John Line and 660 Well Location Unit Letter | NO. |
|--|---|
| DISTRICT.III 1000 Rio Bisson Rd., Assec, NM 87410 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE "APPLICATION FOR PERMIT" (PORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: ON ONLY ON WELL ON OTHER John H. Hendrix Corporation 1. Address of Operator 223 W. Wall, Suite 525, Midland, TX 79701 4. Well Lection Unit Letter : 1980 Feet From The South Line and | |
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOR. USE APPLICATION FOR PERMIT (FORM C. 101) FOR SUCH PROPOSALS) 1. Type of Well: OND OND OND OND I. Hendrix Corporation J. Name of Operator J. Notil Letter I. : 1980. Feel From The South Line and 660. Dri Section J. Sec | STATE FEE X |
| SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: OBL. O | NI & GRS LERSE NO. |
| OTHER: Name of Operator John H. Hendrix Corporation Notice of Operator 223 W. Wall, Suite 525, Midland, TX 79701 Notice of Operator 223 W. Wall, Suite 525, Midland, TX 79701 Notice of Operator Unit Letter I: 1980 Feet From The South Line and 660 Section 23 Township 225 Range 37E NMFM Section 23 Township 225 Range 37E NMFM Section 3318 DF Check Appropriate Box to Indicate Nature of Notice, Report, of SUBSEQUE NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OPNS. TEMPOPRAFILLY ABANDON CHANGE PLANS CASING TEST AND CEMENT & OTHER: Abandon Dri DILL OR ALTER CASING OTHER: OTHER: Abandon Dri Set RBP at 6274'. Set retainer at 5327'. Squeezed Blinebry perfs. 5380-39. Found top of 9-5/8" w/ holes in it. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9-5/8" x. Class C. Cement circ. Drld. out cement at 3320' to 3472' & cement retainer at 28. Perf. Drinkard 6233, 39, 45 & 6251' w/ 2 SPF. Acidized perfs. 6233-6251' w/ 2000 gals. Perfs. commuf. 6233 (1) and indication Blinebry perfs. 5460'. Purds. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will abandon Dri 16. Drid. Out retainer & cement to 6090'. Will ab | Name or Unit Agreement Name |
| John II. Hendrix Corporation John II. Hendrix Corporation 223 W. Wall, Suite 525, Midland, TX 79701 4. Well Location Unit Letter I : 1980 Feet From The South Line and 660 Section 23 Township 225 Range 37E NMFM 10. Elevation (Show whether DF, RKE, RI, GR, etc.) 3318' DF 11. Check Appropriate Box to Indicate Nature of Notice, Report, o NOTICE OF INTENTION TO: SUBSEQUE PERFORM REMEDIAL WORK PLUG AND ABANDON CHANGE PLANS COMMENCE DRILLING OFNS. PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT & COMMENCE DRILLING OFNS. 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated by SEE RULE 1103. Set RBP at 6274'. Set retainer at 5327'. Squeezed Blinebry perfs. 5380- 3. Found top of 9-5/8" w/ holes in it. 4. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9-5/ sx. Class C. Cement circ. Drld. out cement at 3320' to 3472' & cement retainer at 340'. Perf. Drinkard 6233, 39, 45 & 6251' w/ 2 SPF. 7. Acidized perfs. 6233-6251' w/ 2000 gals. Perfs. community of the performance of the set of my knowledge and belief. 1. Browly certify that the Ighormation shows in true and complete to the best of my knowledge and belief. | No. |
| Address of Operator 223 W. Wall, Suite 525, Midland, TX 79701 Drid Well Location Unit Letter _ L : 1980 Feet From TheSouth Line and660 Section | name or Wildcat |
| 23 W. Wall, Suite 525, MIDIANT, IX Well Location Unit Letter _ I : 1980 Feet From TheSouth | nkard |
| Section 23 Township 22S Range 37E NMFM 10. Elevation (Show whether DF, RKB, RI, GR, etc.) 3318' DF 11. Check Appropriate Box to Indicate Nature of Notice, Report, or NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK TEMPORABILY ABANDON CHANGE PLANS CASING TEST AND CEMENT & COMMENCE DRILLING OPNS. PULL OR ALTER CASING OTHER: Abandon Dri 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated by the proposed of the pertinent and the pertinent dates. See the pertinent dates in the pertinent dates of the pertinent dates of the pertinent dates. See the pertinent dates of the pertinent dates of the pertinent dates. 2. Set retainer at 5327'. Squeezed Blinebry perfs. 5380-38. Found top of 9-5/8" w/ holes in it. 3. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9-5/4. 3. Set retainer at 3320' to 3472' & cement retainer at 5233-6251' w/ 2000 gals. Perfs. communification Blinebry perfs. 53460'. 3. Set retainer at 5331' & squeezed perfs. 6233-6251' & F. Set Perfs. Communification for Blinebry Oil completion. Set C-103 files. 1. Interty certify that the promotion above is true and complete to the best of my knowledge and belief. | Feet From TheEast Line |
| PERFORM REMEDIAL WORK TEMPOTARILY ABANDON PULL OR ALTER CASING OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimates). Set RBP at 6274'. Set retainer at 5327'. Squeezed Blinebry perfs. 5380-3. Found top of 9-5/8" w/ holes in it. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9-5/8x. Class C. Cement circ. Drld. out cement at 3320' to 3472' & cement retainer at 3320' to 3472' & cement retainer at 3320' to 3472' & cement retainer at 346'. Perf. Drinkard 6233, 39, 45 & 6251' w/ 2 SPF. Acidized perfs. 6233-6251' w/ 2000 gals. Perfs. communification Blinebry perfs. 536'. Set retainer at 5331' & squeezed perfs. 6233-6251' & Found out retainer at 5331' & squeezed perfs. 6233-6251' & Found out retainer at 5331' & squeezed perfs. 6233-6251' & Found out retainer at 5331' & squeezed perfs. 6233-6251' & Found out retainer & cement to 6090'. Will abandon Dripermission for Blinebry Oil completion. Set C-103 find | Lea |
| COMMENCE DRILLING OPNS. CASING TEST AND CEMENT & OTHER: Abandon Dri Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimate work) SEE RULE 1103. Set RBP at 6274'. Set retainer at 5327'. Squeezed Blinebry perfs. 5380-38. Found top of 9-5/8" w/ holes in it. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9-5/8 xx. Class C. Cement circ. Drld. out cement at 3320' to 3472' & cement retainer at 3320' to 3472' & cement retainer at 3320' to 3472' & cement retainer at 3466'. Perf. Drinkard 6233, 39, 45 & 6251' w/ 2 SPF. Acidized perfs. 6233-6251' w/ 2000 gals. Perfs. communification Blinebry perfs. 5340' down. Also had indication Blinebry perfs. 5460'. Set retainer at 5331' & squeezed perfs. 6233-6251' & Found out retainer & cement to 6090'. Will abandon Dripermission for Blinebry Oil completion. Set C-103 find the permission for Blinebry Oil completion. Set C-103 find the permission for Blinebry Oil complete to the best of my knowledge and belief. | ALTERING CASING |
| OTHER: Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimates). Set RBP at 6274'. Set retainer at 5327'. Squeezed Blinebry perfs. 5380-3. Found top of 9-5/8" w/ holes in it. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9-5/8x. Class C. Cement circ. Drld. out cement at 3320' to 3472' & cement retainer at 3320' to 3472' & cement retainer at 9-5/9. Perf. Drinkard 6233, 39, 45 & 6251' w/ 2 SPF. Acidized perfs. 6233-6251' w/ 2000 gals. Perfs. communification Blinebry perfs. 5340'. Acidized perfs. 6233-6251' & squeezed perfs. 6233-6251' & F. Set retainer at 5331' & squeezed perfs. 6233-6251' & F. Set retainer at 5331' & squeezed perfs. 6233-6251' & F. Set retainer at 5331' and indication Blinebry perfs. 5460'. Drld. out retainer & cement to 6090'. Will abandon Dr. permission for Blinebry Oil completion. Set C-103 fit. | PLUG AND ABANDONMENT K |
| 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimates work) SEE RULE 1103. 1. Set RBP at 6274'. 2. Set retainer at 5327'. Squeezed Blinebry perfs. 5380— 3. Found top of 9–5/8" w/ holes in it. 4. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9–5/ 5. sx. Class C. Cement circ. 6. Drld. out cement at 3320' to 3472' & cement retainer at 3320' to 3472' & cement retainer at 9-2 perf. Drinkard 6233, 39, 45 & 6251' w/ 2 SPF. 7. Acidized perfs. 6233–6251' w/ 2000 gals. Perfs. communification Blinebry perfs. 5340' down. Also had indication Blinebry perfs. 5460'. 8. Set retainer at 5331' & squeezed perfs. 6233–6251' & F. 5460'. 9. Drld. out retainer & cement to 6090'. Will abandon Dranger of the performation above to the best of my knowledge and belief. | |
| 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimate work) SEE RULE 1103. 1. Set RBP at 6274'. 2. Set retainer at 5327'. Squeezed Blinebry perfs. 5380—3. Found top of 9-5/8" w/ holes in it. 3. Perf. 2 sq. holes at 3466'. Cemented fr. 3466' & 9-5/8. Sx. Class C. Cement circ. 5. Drld. out cement at 3320' to 3472' & cement retainer at Perf. Drinkard 6233, 39, 45 & 6251' w/ 2 SPF. 7. Acidized perfs. 6233-6251' w/ 2000 gals. Perfs. communification Blinebry perfs. 5460'. 8. Set retainer at 5331' & squeezed perfs. 6233-6251' & F. S460'. 9. Drld. out retainer & cement to 6090'. Will abandon Dripermission for Blinebry Oil completion. Set C-103 file. | |
| Acidized perfs. 6233-6251' W/ 2000 gdfs. fr. 6340' down. Also had indication Blinebry perfs. 5 fr. 6340' down. Also had indication Blinebry perfs. 5 8. Set retainer at 5331' & squeezed perfs. 6233-6251' & F 5460'. Drld. out retainer & cement to 6090'. Will abandon Dr permission for Blinebry Oil completion. Set C-103 fill Thereby certify that the Information above is true and complete to the best of my knowledge and belief. | 5460' w/250 sx. 8" - 7" annulus w/465 at 5327' & cement to 54 |
| 9. Drld. out retainer & cement to 6090'. Will abandon Dr permission for Blinebry Oil completion. Set C-103 fill permy certify that the information above is true and complete to the best of my knowledge and belief. | Blinebry perfs. 5380- |
| I hereby certify that the lyformation above is true and complete to the best of my knowledge and belief. | rinkard attempt & reque |
| Kinn H Mart Mar mue Vice-President | DATR |
| Signature | (915триятноне но. 684-66. |
| (This apace for State Use) Orig. Signed by Poul Kautz | 1)01 |
| ALTROVED BY TITLE | DATE |