

NO. OF COPIES RECEIVED	
DISTRIBUTION	
ANTA FE	
FILE	
J.S.G.S.	
AND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒	GAS WELL ☐	OTHER ☐
Name of Operator		
Phillips Petroleum Company		
Address of Operator		
Room 711, Phillips Bldg., Odessa, Texas 79761		
Location of Well		
UNIT LETTER	661	FEET FROM THE west LINE AND 1980 FEET FROM
THE south	LINE, SECTION 24	TOWNSHIP 22-S RANGE 37-E NMPM.

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name
Sims
9. Well No.
1
10. Field and Pool, or Wildcat
Drinkard
12. County
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
INFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
ILL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-20-75: MI Baber unit, killed well.
 11-21-75: WIH w/bit & 6 DC's on 2-3/8" tbg, Drld cmt 5490-5504'.
 11-22-75: Drld CIBP at 5504; circ to 6412.
 11-23-75: SD 24 hrs.
 11-24-75: Drld BP at 6412' and cmt to 6422'.
 11-25-75: Drld cmt 6422-60', 6727-66'.
 11-26-75: Drld BP at 6766', circ to 6942'.
 11-27-75: SD 24 hrs.
 11-28-75: Drld cmt/junk f/6942-90'.
 11-29-75: Drld cmt 6990-7013'.
 11-30-75: SD 24 hrs.
 12-1-75: Drld cmt 7013-46'.
 12-2-75: Drld cmt.
 12-3-75: Drld cmt 7223-7322'. Made trip, picked up csg scraper and circ hole w/fresh water.
 12-4-75: Pld 4-3/4" bit & tbg. Schlumberger ran compensated neutron log f/7322-5000'.
 McCullough perf open hole w/1 shot per foot w/strip shot at 7170-7230', 7295-7315', total 82 holes.

Series 900 BOP, 3000# WP, double w/1 set blind rams, 1 set pipe rams; manually operated.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller, Engineering Advisor

DATE 1-12-76

COPIES OF APPROVAL, IF ANY:

JAN 16 1976

- 12-5-75: Set 2-3/8" tbg OE at 7027', Baker R pkr at 7937'. Swbd tbg dry. Dowell treated down tbg thru OH 6974-7322' w/3000 gals 28% HCL acid. Flushed w/44 BW. Max press 2800#, avg press 2200#, ISDP 1800#. Flwd 48 BLW, no acid water.
- 12-6-75: Swbd 9 hrs, 4 BO, 72 BAW, 18 BLW, FL at 6700'.
- 12-7-75: SD 24 hrs.
- 12-8-75: F/3/4 hrs on 3/4" ch, 17 BO, FTP 650# to 0#. Loaded tbg w/30 BW. COOH w/tbg & pkr. Schlumberger perf 5 1/2" csg in Blinebry zone w/1 jet shot per foot at 5527', 5528', 5529', 5558', 5559', 5560', 5629', 5639', 5640', 5641', 5644', 5696', 5701', 5704', 5805', 5807', 5808', 5809', 5812', and 5817'. Perf Drinkard zone w/1 shot/ft at 6356', 6371', 6375', 6383', 6389', 6430', 6446', 6609', 6610', 6640', 6641', 6656', 6662', 6667', 6668', 6669', 6716', 6813', 6818', 6821', 6822', 6823', 6942', 6945', 6953', 6956', 6959', 6962', 6969', 6970', 6971'.
- 12-9-75: WIH w/BP & RTTS, unable to set BP. COOH w/tbg & pkr. WIH w/BP retr tool, pulled BP. Howco set BP at 6900', RTTS pkr at 6890'.
- 12-10-75: Dowell treated Drinkard in 3 stages moving BP&RTTS pkr. 1st: Perfs 6813-90' w/3000 gals 28% acid, flushed w/2% KCL wtr. Max press 1400#, avg press 1400#, ISDP 700#, 10 min SIP 200#. AIR 2.6 BPM. 2nd: Perfs 6609-6716' w/2500 gals 28% acid flushed w/KCL water. Max press 3300#, avg 1000#, ISDP vacuum, AIR 6 BPM. 3rd: Perfs 6356-6446' w/3500 gals 28% acid, flushed w/KCL water. Max press 850#, avg press 800#, ISDP vacuum, AIR 3.8 BPM. Treated Blinebry in 2 stages: 1st: Perfs 5627-5817' w/4250 gals 28% acid flushed w/KCL water. Max press 2100#, avg press 2000#, ISDP 800#, AIR 3.6 BPM. 2nd: Perfs 5430-5556' w/2500 gals 28% acid, flushed w/KCL water. Max press 1300#, avg press 1200#, ISDP vacuum, AIR 3.4 BPM. Lowered BP to 5850', pkr at 5400'. Flwd Blinebry 6 hrs, 20 BO, 160 BW.
- 12-11-75: Flwd Blinebry 8 hrs, 24/64" ch, 35 BO, 80 BAW, FTP 600#. Loaded tbg w/50 BW. Set BP at 6908', RTTS pkr at 6310'.
- 12-12-75: Swbd & flwd Drinkard 9 hrs, 30 BO, 110 BAW. SI 15 hrs, TP 1000#.
- 12-13-75: Flwd Drinkard 4 hrs, 1/2" ch, 4 BO, 30 BAW, FTP 1000#-500#. SI 20 hrs, TP 1000#.
- 12-14-75: SI Drinkard 24 hrs, TP 1000#. SI Blinebry 24 hrs, SICP 100#.
- 12-15-75: Killed well w/75 BW. Pld RTTS & BP. Set 2-3/8" tbg OE at 6880'. Baker F npl at 6062'. Baker R pkr 5999', Baker sleeve closed at 5719'. Swbd Drinkard 2 hrs, 20 BLW, Blinebry SI 24 hrs, CP 150#.
- 12-16-75: Swbd & flwd Drinkard 6 hrs, 10 BO, 80 BAW, FTP 450#. Released Baber unit. Flwd 15 hrs no gauge.
- 12-17-75: F/Drinkard 24 hrs, 12/64" ch, 5 BO, 23 BAW, FTP 750#, Blinebry SI 24 hrs, SICP 240#.
- 12-18-75: Flwd Drinkard 24 hrs, 13/64" ch, 24 BO, 89 BLW, FTP 440#. Opened Blinebry 3 hrs, 1/2" ch. FCP 240# to 0#.
- 12-19-75: F/Drinkard 24 hrs, 13/64" ch, 28 BO, 30 BLW. GOR 16970/1, FTP 440#. Blinebry SI 24 hrs, CP 100#.
- 12-20-75: F/Drinkard 24 hrs, 13/64" ch, 25 BO, 30 BLW, GOR 18210/1, FTP 440#. Blinebry SI 24 hrs CP 180#.
- 12-21-75: Drinkard SI 24 hrs, TP 550#. Blinebry SI 24 hrs, CP 220#.
- 12-22-75: Blinebry open 10 hrs on 1" ch, no gauge, FCP 220# to 0#. SI 14 hrs. Drinkard SI 24 hrs.
- 12-23-75: Flwd Drinkard 24 hrs, no gauge. Blinebry SI 24 hrs, SICP 300#.
- 12-24/28-75: Blinebry SI 120 hrs, PU. Drinkard F/120 hrs, no gauge, FTP 400#.
- 12-29-75: Open Blinebry for 8 hrs, 18/64" ch, flowline leaked. SI to repair flowline. Drinkard SI 24 hrs, TP 800#.
- 12-30-75: Blinebry open 8 hrs, 18/64" ch, CP 450# to 0#, no fluid, no gauge. SI 16 hrs. Drinkard SI 24 hrs, TP 800#.
- 12-31-75: RU Baber unit. Gerald WL set blanking plug in seal npl at 6099'. Opened Baker sleeve at 5719'. Swbd Blinebry 5 hrs, 6 BO, 26 BSW. SI 16 hrs, TP 450#. Drinkard blanked off.
- 1-1-76: Blinebry opened 24 hrs, 24/64" ch, no fluid, TP 450# to 0#. Drinkard blanked off.
- 1-2-76: Swbd Blinebry 9 hrs, 31 BO, 22 BSW. Drinkard SI.
- 1-3-76: Swbd Blinebry 7 hrs, 5 BO, 23 BSW.
- 1-4-76: Blinebry SI 24 hrs, TP 500#; Drinkard SI 24 hrs, CP 550#.
- 1-5-76: Opened Blinebry 2 hrs, 1/2" ch, 3 BO, 14 BSW, FTP 500-0#. Swbd 2 hrs, 8 BLW. SI. Drinkard SI 24 hrs.
- 1-6-76: Drinkard SI 24 hrs. Blinebry flwd 6 hrs, 1/2" ch, 5 BLW & died. SI to PU.