


NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES



Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL		NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL			

Hobbs, New Mexico

Place

11-7-45

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a notice of intention to do certain work as described below at the Phillips Petroleum Company
 Company or Operator Phillips Lease Well No. 1 in NW 1/4 SE 1/4
 of Sec. 24, T. 22S, R. 37E, N. M. P. M., Brinkard Field,
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION

(5½" casing set at 6999'. Hole plugged back with cement to 6942.)

Perforated 5½" casing 6825 to 2690, State Andrews Zone, test with 4-stage acid treatment, (500, 2,000, 5000, and 10,000 gals.);

If unproductive, plug back with cement to 6727, perforate 5½" casing 6430 to 6450, Fullerton Zone, and test with 500 gallons acid;

If unproductive, squeeze off perforations and plug back with cement to 6412, perforate 5½" casing 6355 to 6390, test with 4-stage acid treatment (500, 1500, 2500 and 3500 gals);

If unproductive, squeeze off perforations, drill out cement plug to 6418, perforate casing 6390 to 6410 to test Fullerton Zone;

(Over)

Approved NOV 13 1945, 19
except as follows:

Phillips Petroleum Company
Company or Operator

By [Signature]

Position District Superintendent
Send communications regarding well to

Name O. K. Morris

Address Box 1605

Hobbs, New Mexico

OIL CONSERVATION COMMISSION,
By Roy Yarrborough
Title Oil & Gas Inspector

If unproductive, squeeze off perforations and plug back to 5484, perforate casing 5430 to 5460 to test Clearfork Zone for gas production;

If unproductive, set retainer at 5275 and perforate casing 5145 to 5165 to test Belt Zone by acidizing with 500 gallons;

If unproductive, squeeze off perforations and perforate casing 5085 to 5125 and test with 2-stage acid treatment (500 and 1500 gals.);

If unproductive, squeeze off perforations and perforate casing 3835 to 3860 and test with 500 gallons acid;

If unproductive, squeeze off perforations and drill out cement plugs and retainer to 5485'. Perforate casing 5459 to 5484, acidize Clearfork Zone through perforations 5430 to 5484 with 4-stage treatment (200, 1000, 2000 and 3500 gals.), and complete as gas well.