## DRILL STEM TEST

- 6-8-48 Halliburton took Drill Stem Test 5450-5579 Clear Fork Formation. 3-1/2" drill pipe. 5/8" bottom, 1" top chokes. Tool open 1 hour, air immediately, gas in 3 minutes, did not flow. Recovered 250' gas cut mud, 450' oil and gas cut mud. 15 minutes Bottom Hole Pressure build-up 2650#.
- 6-22-48 Halliburton took Drill Stem Test 6365-6467'. 5/8" bottom, 1" top chokes. 3-1/2" drill pipe. Open 2 hours, air immediately. Gas 17 minutes. Did Not flow. Recovered 360' oil and gas cut mud, 720' clean oil, 360' salt water. 10 minute Bottom Hole Pressure build-up 3250#.

## MEXICO OIL CONSERVATION COM AISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the conservation commission or its proper agent perore the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission. Indicate nature of notice by checking below: NOTICE OF INTENTION TO THE OR CHEMICALLY TREAT WELL NOTICE OF INTENTION TO TEST CASING SHUT-OFF NOTICE OF INTENTION TO PULL OR NOTICE OF INTENTION TO CHANGE PLANS OTHERWISE ALTER CASING NOTICE OF INTENTION TO PLUG WELL NOTICE OF INTENTION TO REPAIR WELL NOTICE OF INTENTION TO DEEPEN WELL Hobbs, New Mexico Date OIL CONSERVATION COMMISSION, Santa Fe, New Mexico. Centlemen: Following is a notice of intention to do certain work as described below at the.... in NW/4 NW/4 Well No. 4 Phillips Petroleum Company Company or Operator Sims Drinkard 37-E , N. M. P. M., Field. of Sec. 24 T. County. FULL DETAILS OF PROPOSED PLAN OF WORK FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION Acidize well through perforations 6390' to 6450' with approximately 10,000 gallens Halliburton 15% acid, treating by stages. Inner string casing set at 2945.23'. Phillips Petroleum Company Approved . Company or Operator except as follows: District Chief Clark Position ... Send communications regarding well to M. C. Croston OIL CONSERVATION COMMISSION, Name \_\_ Address Box 1605 Hobbs, New Mexico