

TRIPPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
NOV 1 1947
RECEIVED

HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		Report on Plug Back	X

OCTOBER 30, 1947

Hobbs, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Gulf Oil Corporation

Ella

Well No. 1

in the

Company or Operator

Lease

C. NE NE

of Sec. 25

T. 22S

R. 37E

N. M. P. M.,

Drinkard

Field,

Lea

County.

The dates of this work were as follows: Work started October 7, 1947; completed October 25, 1947.

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on October 10, 1947

and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Plugged back with 5.81 sacks cement from 6470' to 6467' and also plugged back from 6467' to 6407' with 5 sacks cement and Halliburton Securaloy dump bailer, which was lost in hole. Spotted 100 gallons of Dowell Jelly seal and Flake. Perforated 7" casing from 6355' to 6365' with six 15/32" holes per foot by Lane Wells. Loaded hole with oil. Acidized with 6000 gallons of 15% acid by Dowell, Inc. Flowed 16 ~~max~~ bbls. oil (2% BS & W) through 30/64" choke in 24 hours.

Witnessed by N. B. Jordan Gulf Oil Corporation Foreman
Name Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

30th day of October, 19 47

Name E. J. Gallagher

Position District Sup't.

Representing Gulf Oil Corporation

Company or Operator

My commission expires 10-24-49

Address Box 1667, Hobbs, New Mexico

Remarks: **APPROVED**

NOV 1 1947

Date

Reg. Y. H. H. H. H.
Name
Oil & Gas Inspector

Title