

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Chevron U.S.A. Inc.

3. Address of Operator

P.O. Box 670, Hobbs, NM 88240

4. Well Location

Unit Letter P : 660 Feet From The East Line and 990 Feet From The South Line

Section 25

Township 22S

Range 37E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3324

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: plugback ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD: 7025

PB: 6190

Work performed 3/5/89 thru 3/15/89

MIRU. POH w/prod. equip. Run GR/CCL. RIH w/ CIBP and set at 6225'. Dump 3sx cmt on CIBP. Est TOC at 6190'. Set pkr at 6159 and tst CIBP to 1000psi. ok. Isolate casing leak 3815-3846. PU CIBP and set at 3751'. Tst tbg to 2100psi, ok. Mix and pump 800sx C1 C. Displace w/FW. WOC 26 hrs. DO cmt to 3960. RIH to 3980, tst sqz to 500psi, ok. Perf Blinbry at 5607,13,16,24,28,32,80,91,5712,29, 73 & 78 w/4" guns, 180° phase. 1 JHPF. Acidize Blinbry perfs w/3000 gallons 15% NEFE. Swab. Frac Blinbry perfs w/28,700 gal 40# XL gelled 8.6 CBW. 56,500# 20/40 and 10,000# 20/40 resin coated. Flush w/8.6. Leave well SION. Wait f/frac to heal. Swab. Flow well to test tank f/2 hrs. Pmp 10# BW down tbg. Rel pkr and tag sand at 5973. RIH w/2 3/8" prod. tbg. to 5498'. Pkr at 5498'. Turn over to production dept.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. K. Elmer

TITLE Technical Asst.

DATE 3-23-89

TYPE OR PRINT NAME

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

MAR 28 1989

748 Rm. (hold) E
Sub 010

RECEIVED
MAR 27 1989
OLD
HOBBS OFFICE