

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
APR 24 1953
OIL CONSERVATION COMMISSION

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

April 23, 1953
(Date)Hobbs, New Mexico
(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Western Oilfields, Inc. Amanda Sims
(Company or Operator) (Lease)
J. C. Grain Drilling Co. Well No. 1 in the NE 1/4 SE 1/4 of Sec. 25
(Contractor)
T. 22S, R. 37E, NMPM, Drinkard Pool, Lea County.

The Dates of this work were as follows: April 15-18, 1953

Notice of intention to do the work (was) (was not) submitted on Form C-102 on _____, 19____,
(Cross out incorrect words)
and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We ran 40# 9-5/8" casing in a 12 1/4" hole to total depth of 2800'. At this depth we attempted to cement with 1800 sax. When approximately 1100 sax had been pumped into casing we noted cement returning into cellar. We pumped the plug down and found it stopping at 1762'. We thereupon circulated cement out of hole and attempted to pull casing but was unable to free it. We pumped 600 sax of 6% jel and 100 sax of regular cement into casing and through break at 1762'. Cement circulated back into cellar. We allowed cement to set 24 hours then drilled plug and rotated bit to top of float cellar. We then ran an 8-7/16" reamer in hole to check condition of casing. Reamer followed easily to top of float cellar. We then drilled float cellar with 8-1/4" bit and cleaned cement out to top of float shoe. We perforated casing with three 1/2" holes at 2785'; set a cement retainer at 2743' and squeezed through perforations with 100 sax of regular cement. Allowed cement a set time of 24 hours then pressure tested casing with 1000# for 30 minutes. Pressure drop was very slight and cement job was therefore considered to be O K. Drilled shoe, then drilled ahead.

Witnessed by Dick Gaston J. C. Grain Drilling Co. Drilling Sup't.
(Name) (Company) (Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name: Charles P. Miller

Position: Agent

Representing: Western Oilfields, Inc.

Address: 1636 Stout Street, Denver, Colorado

Roy Yachroeg
(Name)
(Title)

APR 24 1953
(Date)