NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCD-HOBBS
1-MR. FRNKA-TULSA
1-MR. A. B. CARY-MIDLAND
1-PJB, ENGR.
1-ARCO, MIDLAND

1-FILE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease: State [ ] Fee [X]

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

7. Unit Agreement Name

OIL WELL [X] GAS WELL [ ] OTHER-

Name of Operator: Getty Oil Company

8. Farm or Lease Name: Baker A

Address of Operator: P. O. Box 730, Hobbs, NM 88240

9. Well No.: 4

Location of Well: UNIT LETTER C, 660 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 26 TOWNSHIP 22-S RANGE 37-E NMPM.

10. Field and Pool, or Wildcat: Langlie-Mattix

15. Elevation (Show whether DF, RT, GR, etc.): 3330' DF

12. County: Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK [ ]
- TEMPORARILY ABANDON [ ]
- PULL OR ALTER CASING [ ]
- PLUG AND ABANDON [ ]
- CHANGE PLANS [ ]
- OTHER [ ]

SUBSEQUENT REPORT OF:

- REMEDIAL WORK [ ]
- COMMENCE DRILLING OPNS. [ ]
- CASING TEST AND CEMENT JOB [ ]
- ALTERING CASING [ ]
- PLUG AND ABANDONMENT [ ]
- OTHER Squeeze water flow and acidize [X]

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

/10/80 MIRU DA&S.

/11 Pulled rods and tbg. Ran 4 3/4" bit and scrapper to 2953'. Pulled and laid down scrapper. Ran 4 3/4" bit and tagged at 2953'.

/12 Ran 4 3/4" impression block - tagged 2953'. Showed collapsed. Ran 4 1/2" swage bumper sub and tagged at 2953'. Swaged to 2959'. Pulled swage.

/13 Ran 2 7/8" x 4 3/4" taper mill. Milled out bad 5 1/2" csg. 2954-2967'.

/14 Lowered 4 3/4" taper mill and tagged at 2967'. Milled to 2979 (total 25'). Pulled mill - worn out.

/15 SD.

/16 Ran 4 3/4" taper mill and tagged at 2979' (made 6"). Milled to 2977'. Pulled mill. Ran 4 3/4" bit and tagged at 2975'. Drilled and made 6".

(CONTINUED ON BACK)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ED. Dale R. Crockett TITLE Area Superintendent DATE 7/17/80

Dale R. Crockett

Orig. Signed By
John Runyan
Geologist

OVED BY TITLE DATE JUL 22 1980

DITIONS OF APPROVAL, IF ANY:

DE/