

Baker "A"
Well No. 4
Lea County, New Mexico
Page 2

- 13) Frac treated perforations 3488-3566' with 33,000 gallons of 9# gelled brine water, 45,000# of 20/40 sand, using 8 ball sealers.
- 14) Flowed 24 hours, no oil, 206 barrels of load water.
- 15) Pulled bridge plug at 3580' and packer at 3239'.
- 16) Ran 117 joints (3641) of 2-3/8" OD 4.7# tubing, set at 3651'.
- 17) Ran rods and pump.
- 18) Pump tested well from September 29 to October 9, 1973.
- 19) Pumped 24 hour test October 10, 1973, producing 5 barrels of oil, 6 barrels of water, and 25 MCFGPD from Queen (Penrose) Sand perforations 3488-3647'.

- 13) From treated perforations 3488-3566' which 13,000 gallons of 4% gelled brine water
 45,000% of 70/40 sand, using 8 ball sealers.
- 14) Flowed 24 hours, no oil, 100 barrels of load water.
- 15) Packed bridge plug at 3580' and packed at 3590'.
- 16) Ran 11V joints (3641) of 2-7/8" OD 4.75 tubing, set at 3621'.
- 17) Ran rods and pump.
- 18) Pump tested well from September 29 to October 2, 1973.
- 19) Pumped 14 hour test October 10, 1973, producing 5 barrels of oil, 6 barrels of water,
 and 25 MCTGP from Green (Penrose) Sand perforations 3488-3647'.