

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	165'	165'	Red Bed and Sand
165'	438'	270'	Red Shale and Sand
435'	638'	203'	Red Rock, Shale and Sand
638'	721'	83'	Red Rock and sand
721'	1140'	419'	Red Rock
1140'	1260'	120'	Anhydrite
1260'	1285'	25'	Red Rock
1285'	1324'	39'	Broken Red Rock, Anhydrite and Salt
1324'	1423'	99'	Red Rock
1423'	1435'	12'	Red Rock and Anhydrite
1435'	1490'	55'	Anhydrite
1490'	1501'	11'	Salt
1501'	1690'	189'	Red Rock and Anhydrite
1690'	1918'	228'	Anhydrite, Salt and Potash
1918'	2065'	147'	Salt and Potash
2065'	2161'	96'	Anhydrite, Salt and Potash
2161'	2261'	100'	Anhydrite and Salt
2261'	2300'	39'	Salt, Anhydrite and Gypsum
2300'	2388'	88'	Anhydrite and Salt
2388'	2425'	37'	Anhydrite, Red Rock and Salt
2425'	2480'	55'	Red Rock and Salt
2480'	2513'	33'	Anhydrite
2513'	2543'	30'	Brown Lime
2543'	2574'	31'	Anhydrite
2574'	2580'	6'	Lime
2580'	2583'	3'	Sand
2583'	2599'	16'	Anhydrite and Lime
2599'	2647'	48'	Lime
2647'	2682'	35'	Anhydrite and Lime
2682'	2864'	182'	Anhydrite
2864'	3340'	476'	Lime (Broken and streaked)
3340'	3345'	5'	Sand
3345'	3415'	70'	Lime, Brownish and broken
3415'	3545'	130'	Grey Lime
3545'	3550'	5'	Grey Lime w/ Gas and Oil Show
3550'	3565'	15'	Grey Lime
3565'	3567'	2'	Grey, Sandy Lime w/ Gas Increase
3567'	3577'	10'	Grey, Hard Lime
3577'	3581'	4'	Grey, Sandy Lime w/ Gas and Oil Increase
3581'	3592'	11'	Grey, Soft Sandy Lime . 2000' OIH w/ Gas estimated 50,000 cu.ft.
3592'	3600'	8'	Grey, Soft Sandy Lime, flowing by heads every three hours, est 4 bbls per head, gas estimated 100,000 cu.ft.
3600'	3610'	10'	Gray Lime.