Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

						!
PORT ON BEGINNING DRILLING OPERATIONS		REPOR'	r on repair	ING WELL		
PORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPOR'	ON PULLIN	G OR OTHER	RWISE	
PORT ON RESULT OF TEST OF CASING SHUT-OFF	*	REPOR	r on deepen	ING WELL		
PORT ON RESULT OF PLUGGING OF WELL		•				
	Hob bs	New	Mexico	August	25,	1937
L CONSERVATION COMMISSION, nta Fe, New Mexico. ntlemen:		Place			Date	
llowing is a report on the work done and the re	sults obtaine	17 -		oted above a Well No	t the 5	in the
Company or Operator	<del></del>	Lease				
SE NW of Sec. 27	, т	6 8	, R.	37	<del></del> ,	N. M. P. M.
Penrose Area Field,	st 15.	1937				County.
	-			A > 2 = 2 = 2	+ 16	19 37
tice of intention to do the work was [	submitted (	on Form	C-102 on	27/10/2 212	<u> </u>	19 0 :
d approval of the proposed plan was [ ot]	obtained. ((	Tross out	incorrect wor	·ds )		
a approvar of the proposed plan was [		JI OBB OUL	Incorrect wor	us.,		
DETAILED ACCOUNT OF V  After allowing cement for casing shut-off i buston process at 339 OK and are now drilli	to set in 7" 0	one and drill D cast sing	D RESUL'	rs OBTAI	sted	DUI
After allowing cement for casing shut-off i buston process at 339	to set in 7" 0	one and drill D cast sing	D RESUL'	and te	sted i-	DUPLIC
After allowing cement for casing shut-off i buston process at 339	to set in 7" 0	one and dril. D cas: sing d	D RESULIDE RESULING Set Shut-off	rs OBTAI	sted i-	DUPL CA
After allowing coment for casing shut-off i buston process at 339 OK and are now drilli	vork do	one Andril. Docas: sing d. Compan	led plug ing set shut-of f	and te by Hall tested	sted 1- 937	// Z
After allowing cement for casing shut-off is buston process at 339 OK and are now drilling the state of the s	vork do	one and company	led plug ing set shut-of f	and te by Hall tested	sted 1- 937	fitle
After allowing coment for casing shut-off is buston process at 339 OK and are now drilling the state of the s	VORK DO	one and company one and compan	led plug ing set shut-off	and temperature of the state of	sted 1- 937 ormation	ritle given above
After allowing cement for casing shut-off is buston process at 339 OK and are now drilling the state of the s	VORK DO	one and company	led pluging set shut-of f	and temperature of superature	sted 1- 937 pan ormation	fitle
After allowing cement for casing shut-off is buston process at 339 OK and are now drilling the state of the s	VORK DO	one and company one and compan	led pluging set shut-of f	and temperature of Superature	937 pany	n given above
After allowing cement for casing shut-off is buston process at 339 OK and are now drilling the state of the s	Davidso  I he is to Nar  Pos  Reg	one Andril  Docasi  sing  Compan	led pluging set shut-off	and temperature of superature	937 ormation	n given above