

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

August 1, 1938
Date

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as:

DUPLICATE
of a well to be known as

Skelly Oil Co. J. V. Baker Well No. 6 in CSW NE
Company or Operator Lease
of Sec. 27 1/2, T. 22S, R. 37E, N. M. P. M., Penrose Area Field, Lea County.
N. The well is 1980 feet from S1 of the North line and 1980 feet

[illegible]

AREA 640 ACRES
LOCATE WELL CORRECTLY

The well is 1980 feet [N] [S.] of the North line and 1980 feet [E] [W.] of the East line of Section 27 -

(Give location from section or other legal subdivision lines. Cross out wrong directions.).

If state land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is J. V. Baker

Address Elunice, New Mexico

If government land the permittee is _____

Address _____

The lessee is _____

Address _____

We propose to drill well with drilling equipment as follows:

Cable tools from surface to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:_____

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
18"	16" OD	30#	SH	145'	Cemented	100
15"	13"	40#	SH	425'	Landed	
12-1/4"	10-3/4"	40#	SH	820'	Landed	
10-5/8"	8-5/8"	28#	SH	1225'	Cemented	150
8-1/4"	7" OD	24#	New	3410'	Cemented	200

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3540 feet.

Additional information: In cementing the 16" OD casing the cement will be circulated back to bottom of cellar. At the time the 8-5/8" OD Casing is set and cemented the other casing which was landed, 13" OD and 10-3/4" OD, will be pulled. Before drilling plug on each string the cement shall be given sufficient time to thoroughly set.

Approved _____ **AUG 4 - 1938** _____ 19____
except as follows:

Sincerely yours,

~~Skelly Oil Company~~
Company or Operator

By
Position District Superintendent
Send communication regarding well to
Name Skelly Oil Co.
Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By Ross Walker Jr
Title Oil & Gas Inspector

