



## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	13	13	Cellar
13	25	12	Caliche
25	120	95	Quick Sand
120	135	15	Water Sand
135	142	7	Red Shale
142	145	3	Lime
145	192	47	Red Shale
192	210	18	Sand
210	225	15	Red Rock
225	230	5	Gyp
230	700	470	Red & Blue Shale
700	755	55	Anhydrite
755	765	10	Water Sand
765	790	25	Anhydrite
790	830	40	Sandy Lime
830	1133	303	Red Rock
1133	1240	107	Anhydrite
1240	1270	30	Red Rock & Shells
1270	1285	15	Lime
1285	1290	5	Red Rock
1290	1720	430	Salt & Anhydrite
1720	1765	45	Red Rock
1765	1995	230	Salt & Anhydrite
1995	2090	95	Red Rock & Salt
2090	2295	205	Anhydrite & Salt
2295	2315	20	Lime
2315	2485	170	Salt & Anhydrite
2485	2860	375	Lime
2860	2920	60	Shale & Shells
2920	3548	628	Lime
3548	3586	38	Sand
3586	3610	24	Lime

## TUBING RECORD

2" tubing swung 2½ feet off bottom. Bottom joint perforated 20 feet from bottom up 6 feet with 4 rows of 3/8" holes on 4" centers. Bull plugged on bottom with 2-¼" holes in plug. 1-¼" hole in tubing 10 feet from bottom.