

Submit 3 Copies to Appropriate District Office

State of New Mexico
Enr Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO. 30-025-10500

5. Indicate Type of Lease
STATE FEE

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Christmas

8. Well No. 3

9. Pool name or Wildcat
SWD: San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL GAS WELL OTHER Disposal

2. Name of Operator
148431 Gold Star SWD Ltd. Co.

3. Address of Operator
P.O. Box 1480 Eunice, N.M. 88231

4. Well Location
Unit Letter B : 330 Feet From The N Line and 2310 Feet From The E Line
Section 28 Township 22S Range 37E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- PULL OR ALTER CASING
- OTHER:
- PLUG AND ABANDON
- CHANGE PLANS

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING CPNS.
- CASING TEST AND CEMENT JOB
- OTHER: SWD 606
- ALTERING CASING
- PLUG AND ABANDONMENT

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-1-95 Drill CIBP at 4060'. Run Baker AD-1 Packer. Set at 3850'. Csg. did not test. Shut down.

11-16-95 Pull packer. Run 5" bit and scraper. Run 7" bit and scraper. Run 5" RBP. and 5" packer. Test top of 5" liner to 3850', held 500 psi. Run 7" packer, test top of 5" liner. Held 500 psi. Found hole in 7" between 1414-1445. Shot holes at 1460'. Circulate hole and dye 1/2 bbl. to circulate. Pump 315 sk. class C cement w/2% cacl. Temperature survey shows cement 1000 ft. from surface. Drill out cement. Test csg. 500 psi- Held OK Pull RBP. Run 2 3/8 new Rice fiberglass internal coated tubing w/ Baker loc set nickel plated packer. Displace hole w/ packer fluid. Set packer at 3850'. Test csg 500 psi Held OK, chart attached. Rig down 11-25-95. Expect to start disposing of water 12-20-95

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Royce Crowell TITLE member DATE 12-8-95

TYPE OR PRINT NAME Royce Crowell TELEPHONE NO. 505-394-2504

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT SUPERVISOR

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JAN 12 1995

JCBx

@CIBP
6/16

7A N ... dp

