

OPERATOR

LEASE

Gulf Oil Corporation

A.L. Christmas

WELL NO.

FOOTAGE LOCATION

SECTION

TOWNSHIP

RANGE

1

1780' FNL and 1980' FNL

28

22 South

37 East

Schematic

Tabular Data

Surface Casing

Size 8 5/8" " Depth 1160 ' Cemented with 50Q
TOC Surface feet determined by Circulate
Hole size 12 1/2"

Intermediate Casing

Size None " Depth ' Cemented with
TOC feet determined by
Hole size

Long string

Size 5 1/2" " Depth 6699 ' Cemented with 1925
TOC Surface feet determined by Circulate
Hole size 7 5/8"

Total depth 6700' ' Elevation 3350'GL '
Production Interval: From *' To '

Plugging Operations:

Surface casing pulled: Size Amount 0
Top of stub '

Long String Casing pulled: Size " Amount 0
Top of stub '

Cement plugs:

1.	Amount	<u>10</u>	sx	From	<u>5075</u>	'	To	<u>5175</u>
2.	Amount	<u>10</u>	sx	From	<u>3872</u>	'	To	<u>3972</u>
3.	Amount	<u>10</u>	sx	From	<u>3366</u>	'	To	<u>3466</u>
4.	Amount	<u>20</u>	sx	From	<u>2346</u>	'	To	<u>2546</u>
5.	Amount	<u>20</u>	sx	From	<u>1100</u>	'	To	<u>1300</u>
6.	Amount	<u>60</u>	sx	From	<u>Surface</u>		To	<u> </u>

Bridge plug Set: Type ** Depth

Fluid in Hole P & A Mud

* Drinkard 6458' - 6575'
Tubb 6108' - 6265'
Blaineby 5489' - 5907'
Paddock 5123' - 5309'

** CIBP @ 6390' with 35' Cement
CIBP @ 6050' with 35' Cement
CIBP @ 5467' with 35' Cement

Drilling Completed 2-15-77.

8 5/8"@1160'

5 1/2"@6699'

Total Depth 6700'

RECEIVED

MAY 22 1995
JOE HOBBS
OFFICE