

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

ROTARY TOOLS WERE USED FROM Surface FEET TO 3725 FEET, AND FROM FEET TO 942 FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

PUT TO PRODUCE. October 28, 1959.

OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 376 BARRELS OF LIQUID OF WHICH 100 % WAS OIL; - % WAS EMULSION; - % WATER; AND - % WAS SEDIMENT. A.P.I. GRAVITY 35.4

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS _____ M.C.F. PLUS _____
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE _____ LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

NORTHWESTERN NEW MEXICO

T. ANHY.	1160	T. DEVONIAN	T. OJO ALAMO
T. SALT		T. SILURIAN	T. KIRTLAND-FRUITLAND
B. SALT		T. MONTOYA	T. FARMINGTON
T. YATES	2702	T. SIMPSON	T. PICTURED CLIFFS
T. 7 RIVERS	2890	T. McKEE	T. MENESEE
T. QUEEN	3443	T. ELLENBURGER	T. POINT LOOKOUT
T. GRAYBURG	3713	T. GR. WASH.	T. MANCOS
T. SAN ANDRES		T. GRANITE	T. DAKOTA
T. GLORIETA		T.	T. MORRISON
T. DRINKARD		T.	T. PENN.
T. TUBBS		T.	T.
T. ABO		T.	T.
T. PENN.		T.	T.
T. MISS		T.	T.

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	310	310	Surface Rock & Red Bed				
310	730	420	Red Bed				
730	1090	360	Red Bed and Anhydrite				
1090	1280	190	Anhydrite				
1280	2500	1220	Anhydrite and salt				
2500	3202	702	Anhydrite and gyp				
3202	3508	306	Anhydrite and lime				
3508	3725TD	217	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

December 8, 1959

COMPANY OR OPERATOR Humble Oil & Refining Company

ADDRESS Box 2347 - Hobbs, New Mexico (DATE)

NAME R R ALWORTH

POSITION OR TITLE: Agent