

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-934

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Kirby Exploration Co. of Texas	8. Farm or Lease Name New Mexico State M & L
3. Address of Operator P. O. Box 1885, Eunice, NM 88231	9. Well No. 21
4. Location of Well UNIT LETTER G, 1980 FEET FROM THE North LINE AND 2080 FEET FROM THE East LINE, SECTION 29 TOWNSHIP 22S RANGE 37E NMPM.	10. Field and Pool, or Wildcat Langlie Mattix
15. Elevation (Show whether DF, RT, GR, etc.) 3371 DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12/04/85 2-7/8" csg parted @ 434' from surface, work with well bore several days attempting to get down to fish and could not.

12/10/85 TIH w/7-5/8" cement retainer and set @ 249', pump 400 sx Class "C" + 3% Calcium chloride @ 2 BPM @ 300 psig, sting out of retainer, SD, WOC.

12/11/85 Sting into retainer, pump 100 sx Class "C" Neat cement @ 2 BPM @ 500 psig, sting out of retainer, circulate cement from 249' (above retainer) to surface. Place dry hole marker on wellhead, clean location.

\*\* Verbal approval per Mr. Eddie Seay.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Donnie New TITLE Area Superintendent DATE 12-16-85

APPROVED BY [Signature] TITLE OIL & GAS INSPECTOR DATE APR 24 1986

CONDITIONS OF APPROVAL, IF ANY: