

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3735 FEET, AND FROM HOBBS OFFICE 000 FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

PRODUCTION

1960 SEP 13 AM 9:45

PUT TO PRODUCING September 1, 1960

OIL WELL: THE PRODUCTION DURING THE FIRST ~~24~~¹ HOURS WAS 130 BARRELS OF LIQUID OF WHICH 58 %

WAS OIL; _____ % WAS EMULSION; 42 % WATER; AND _____ % WAS
SEDIMENT. A.P.I. GRAVITY 28°

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS _____ M.C.F. PLUS _____

BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE_____LBS.

LENGTH OF TIME SHUT IN _____

PLEASE INDICATE BELOW FORMATION TOPS (in Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO

NORTHWESTERN NEW MEXICO

T. ANHY	T. DEVONIAN	T. OJO ALAMO
T. SALT	T. SILURIAN	T. KIRTLAND-FRUITLAND
B. WY Rustler 1155	T. MONTOYA	T. FARMINGTON
T. YATES 2688	T. SIMPSON	T. PICTURED CLIFFS
T. 7 RIVERS 2828	T. McKEE	T. MENEFEE
T. QUEEN 3420	T. ELLENBURGER	T. POINT LOOKOUT
T. GRAYSON Penrose 3535	T. GR. WASH	T. MANCOS
T. SOLVAY Grayburg 3728	T. GRANITE	T. DAKOTA
T. GLORIETA	T.	T. MORRISON
T. DRINKARD	T.	T. PENN
T. TUBBS	T.	T.
T. ABO	T.	T.
T. PENN	T.	T.
T. MISS	T.	T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	581	581	Redbed				
581	2650	2069	Salt & anhydrite				
2650	3277	627	Lime & Anhydrite				
3277	3735	458	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

September 12, 1960

COMPANY OR OPERATORHumble Oil & Refining Company

ADDRESS BOX 2347
POBBS NEW MEXICO

(DATE)

ORIGINAL
NAME SIGNED ARVIN D. EADY

POSITION OR TITLE	Agent
-------------------	-------