

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3730 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM 000 FEET TO FEET.

PRODUCTION

PUT TO PRODUCING October 6, 1960 1960 DEC 27 AM 7:25
OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 270 BARRELS OF LIQUID OF WHICH 100 %
WAS OIL, % WAS EMULSION, % WATER, AND % WAS
SEDIMENT. A.P.I. GRAVITY 31.5

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.
LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO		NORTHWESTERN NEW MEXICO	
T. ANHY	T. DEVONIAN	T. OJO ALAMO	
T. SALT	T. SILURIAN	T. KIRTLAND-FRUITLAND	
B. Rustler 1178	T. MONTROYA	T. FARMINGTON	
T. YATES 2728	T. GIMPSON	T. PICTURED CLIFFS	
T. 7 RIVERS 2878	T. McKEE	T. MENESEE	
T. QUEEN 3455	T. ELLENBURGER	T. POINT LOOKOUT	
T. Penrose 3590	T. GR. WASH	T. MANCOS	
T. SAN ANDRES	T. GRANITE	T. DAKOTA	
T. GLORIETA	T.	T. MORRISON	
T. DRINKARD	T.	T. PENN	
T. TUBBS	T.	T.	
T. ABO	T.	T.	
T. PENN	T.	T.	
T. MISS	T.	T.	

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	970	970	Redbed				
970	1173	203	Sand				
1173	1200	27	Anhy & shale				
1200	1267	67	Sand				
1267	2636	1369	Anhy & salt				
2636	2737	101	Sandy lime				
2737	2893	156	Lime				
2893	2990	97	Anhy & lime				
2990	3730	740	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

December 23, 1960
COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Box 2347, Hobbs, New Mexico
NAME ARVIN D. Eady POSITION OR TITLE Agent

