

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3740 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

PRODUCTION

PUT TO PRODUCING February 9, 1961
OIL WELL: THE PRODUCTION DURING THE FIRST 5 HOURS WAS 78 BARRELS OF LIQUID OF WHICH 100% WAS OIL; % WAS EMULSION; % WATER; AND % WAS SEDIMENT. A.P.I. GRAVITY 32.1°

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO			NORTHWESTERN NEW MEXICO		
T. ANHY			T. DEVONIAN		T. OJO ALAMO
T. SALT			T. SILURIAN		T. KIRTLAND-FRUITLAND
B. XXX Rustler 1160			T. MONTOYA		T. FARMINGTON
T. YATES 2710			T. SIMPSON		T. PICTURED CLIFFS
T. 7 RIVERS 2855			T. McKEE		T. MENEFEE
T. QUEEN 3434			T. ELLENBURGER		T. POINT LOOKOUT
T. GRAYSON Penrose 3560			T. GR. WASH		T. MANCOS
T. SAN ANDRES			T. GRANITE		T. DAKOTA
T. GLORIETA			T.		T. MORRISON
T. DRINKARD			T.		T. PENN
T. TUBBS			T.		T.
T. ABO			T.		T.
T. PENN			T.		T.
T. MISS			T.		T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	300	300	Surface clay and shells.				
300	1004	704	Red bed.				
1004	1226	222	Red bed and anhydrite.				
1226	1260	34	A nhydrite.				
1260	2635	1375	Salt and anhydrite.				
2635	3530	895	Anhydrite and gyp.				
3530	3598	68	Sand and lime.				
3598	3650	52	Lime.				
3650	3740	90	Lime and sand.				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

March 8, 1961

COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Box 2347, Hobbs, New Mexico (DATE)
NAME [Signature] POSITION OR TITLE Agent