

- IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3732 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM HOBBS OIL FIELD FEET TO FEET.

PRODUCTION

PUT TO PRODUCING April 19, 1961

1961 MAY 31 AM 5:49

OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 184 BARRELS OF LIQUID OF WHICH 100 %
WAS OIL; % WAS EMULSION; % WATER; AND % WAS
SEDIMENT. A.P.I. GRAVITY 31.0°

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO

NORTHWESTERN NEW MEXICO

T. ANHY	T. DEVONIAN	T. OJO ALAMO
T. SALT	T. SILURIAN	T. KIRTLAND-FRUITLAND
B. NA Rustler 1206	T. MONTOYA	T. FARMINGTON
T. YATES 2740	T. SIMPSON	T. PICTURED CLIFFS
T. 7 RIVERS 2884	T. McKEE	T. MENEFFEE
T. QUEEN 3464	T. ELLENBURGER	T. POINT LOOKOUT
T. CRAB Penrose 3575	T. GR. WASH	T. MANCOS
T. SAN ANDRES	T. GRANITE	T. DAKOTA
T. GLORIETA	T.	T. MORRISON
T. DRINKARD	T.	T. PENN
T. TUBBS	T.	T.
T. ABO	T.	T.
T. PENN	T.	T.
T. MISS	T.	T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	240	240	Surface Rock				
240	295	55	Red Bed				
295	536	241	Red Bed and Sand				
536	1046	510	Red Bed and Anhydrite				
1046	1350	304	Anhydrite				
1350	2561	1211	Anhydrite and Salt				
2561	3668	1107	Anhydrite and Gyp.				
3668	3722	54	Anhydrite and Lime				
3722	3732	10	Dolomite.				
	TD						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

May 27, 1961

COMPANY OR OPERATOR Humble Oil & Refining Company

ADDRESS Box 2347, Hobbs, New Mexico

NAME POSITION OR TITLE Agent