

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3758 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM HOBBS OFFICE FEET TO FEET.

PRODUCTION

PUT TO PRODUCING April 25 19 61 1961 MAY 31 AM 5:49
OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 50 BARRELS OF LIQUID OF WHICH 100 %
WAS OIL; % WAS EMULSION; % WATER; AND % WAS
SEDIMENT. A.P.I. GRAVITY 31.2°

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.
LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO

T. ANHY
T. SALT
B. Rustler 1228
T. YATES 2795
T. 7 RIVERS 2947
T. QUEEN 3535
T. Penrose 3650
T. SAN ANDRES
T. GLORIETA
T. DRINKARD
T. TUBBS
T. ABO
T. PENN
T. MISS

T. DEVONIAN
T. SILURIAN
T. MONTOYA
T. SIMPSON
T. McKEE
T. ELLENBURGER
T. GR. WASH
T. GRANITE
T.
T.
T.
T.
T.

NORTHWESTERN NEW MEXICO

T. OJO ALAMO
T. KIRTLAND-FRUITLAND
T. FARMINGTON
T. FICTURED CLIFFS
T. MENESEE
T. POINT LOOKOUT
T. MANCOS
T. DAKOTA
T. MORRISON
T. PENN
T.
T.
T.
T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1162	1162	Red Bed and Red Rock				
1162	1364	202	Anhydrite				
1364	2575	1211	Anhydrite and Salt				
2575	3322	747	Anhydrite and Gyp.				
3322	3536	214	A nhydrite and Lime				
3536	3758	222	Lime				
	TD						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HEREWITH IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

May 27, 1961

COMPANY OR OPERATORHumble Oil & Refining Company ADDRESS Box 2347, Hobbs, New Mexico
NAME POSITION OR TITLE Agent