

RECORD OF DRILL-STEM AND SPECIAL TESTS

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO No Drill Stem Tests

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 3850 FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO 51 FEET.

PRODUCTION

PUT TO PRODUCING July 16, 1959

OIL WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS 27.62 BARRELS OF LIQUID OF WHICH 15 % WAS OIL, % WAS EMULSION, 85 % WATER, AND % WAS SEDIMENT. A.P.I. GRAVITY 23.9

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO

T. ANHY
T. SALT
B. SALT
T. YATES 2802
T. 7 RIVERS 2970
T. QUEEN 3508
T. GRAYBURG 3800
T. SAN ANDRES
T. GLORIETA
T. DRINKARD
T. TUBBS
T. ABO
T. PENN
T. MISS

T. DEVONIAN
T. SILURIAN
T. MONTOYA
T. SIMPSON
T. McKEE
T. ELLENBURGER
T. GR. WASH
T. GRANITE
T.
T.
T.
T.
T.
T.

NORTHWESTERN NEW MEXICO

T. OJO ALAMO
T. KIRTLAND-FRUITLAND
T. FARMINGTON
T. PICTURED CLIFFS
T. MENESEE
T. POINT LOOKOUT
T. MANCOS
T. DAKOTA
T. MORRISON
T. PENN
T.
T.
T.
T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	223	223	Surface Rock				
223	889	666	Red Bed				
889	1176	287	Red Bed & Red Rock				
1176	1450	274	Red Rock & Anhydrite				
1450	2631	1181	Salt & Anhydrite				
2631	3430	799	Anhydrite & Cyp				
3430	3850	420	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HEREWITH IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

August 6, 1959

COMPANY OR OPERATOR Humble Oil & Refining Company
ORIGINAL
NAME SIGNED R. R. ALWORTH

ADDRESS Box 2347 - Hobbs, New Mexico
POSITION OR TITLE Agent