

COPIES

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Notice of Intention to Drill

RECEIVED

JUN 19 1942

HOBBS OFFICE

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

HOBBS, NEW MEXICO

JUNE 16, 1942

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.
Gentlemen:

Place

Date

You are hereby notified that it is our intention to commence the drilling of a well to be known as

SKELLY OIL COMPANY

KING "A"

Well No. 4

in SW SW

Company or Operator

Lease

of Sec. 33

T. 22

R. 37

N. M. P. M.

Skelly

Field, Lea

County

N.

The well is 720 feet (N.) of the south line and 660 feet (E.) of the West line of Section 33.

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is B.L. King

Address Eunice, New Mexico

If government land the permittee is

Address

The lessee is SKELLY OIL COMPANY

Address HOBBS, NEW MEXICO

We propose to drill well with drilling equipment as follows: L.G. Ashley

Cable tools to depth of approximately 3700'. J. G. Ashley, Contractor
Eunice, N.M.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
18"	16"	70#	SH	120'	Cemented	100-to surface
15 1/2"	13"	45#	SH	425'	Landed	
12 1/2"	10-3/4"	40	SH	725'	Landed	
10"	8-5/8"	32#	SH	1100'	Landed	
8 1/2"	7"	20#	New	3375'	Cemented	250

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 3475 feet.

Additional information: Will cement 16" string and circulate cement to surface. The 13", 10-3/4" and 8-5/8" casing will be pulled when 7" oil string is cemented. Halliburton process to be used for cementing.

JUN 19 1942

Approved _____, 19____
except as follows:

"APPROVAL CONDITIONED UPON
COMPLIANCE WITH REQUIREMENTS
OF OPC-WPE."

Sincerely yours,

SKELLY OIL COMPANY

Company or Operator

By

Position District Superintendent

Send communication regarding well to

Name

Skelly Oil Co.

Address

Hobbs, N.M.

OIL CONSERVATION COMMISSION,

By

Title Oil & Gas Inspector

1A21907

~~SECRET~~

NAME	ADDRESS	CITY	STATE	ZIP
Mr. J. H. H. H.	1234 Main St.	Anytown	CA	90210
Mr. J. H. H. H.	1234 Main St.	Anytown	CA	90210

1. The first step in the process is to identify the problem or issue that needs to be addressed. This involves gathering information and understanding the context of the problem.

1. The first step is to identify the problem or question that needs to be answered. This involves understanding the context and the specific information required.

100-443887-1000