

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Submit 3 Copies
to Appropriate
District Office

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator

TEXACO PRODUCING INC

3. Address of Operator

P.O. Box 728 HOBBS, NM 88240

4. Well Location

Unit Letter K : 1980 Feet From The SOUTH Line and 1980 Feet From The WEST Line

Section 33

Township 22S

Range 37 E

NMPM

LEA

County

10. Elevation (Show whether DP, RKB, RT, GR, etc.)

3350 DF

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

COMMENCED WORK 5-11-89, MTRU PULLING UNIT, 70H W/ RODS, PMP, AND TUBING,
TTH W/ 6 1/4" MT BIT, DC'S, AND 2 7/8" WS. CLEAN OUT OPEN HOLE INTERVAL TO TD (3710').
RUN GR-CNL-CALIPER FROM 3709' TO SURFACE, RUN GR-CASING INSPECTION LOG FROM 3388' TO 1000'.
TTH W/ 7" PKR AND 2 7/8" TGG, SET PKR @ 3291'.
ACTIVATE OPEN HOLE INTERVAL FROM 3388' TO 3710' W/ 4000 GAL 15% NEFE ACID IN 4 STAGES
USING 2000" ROCK SALT IN 10 PPG GELLED BETWE TO DIVER, FLUSH W/ 61 GALS 2% KEL
MAXP 1650 PSI, MINP 1200 PSI, AR 40BPM, AP 1450 PSI, ISTP 1200 PSI, 15MIN SI 1100 PSI
FRAC OPENHOLE INTERVAL FROM 3388' TO 3710' W/ 40,000 GAL 40% XL GEL CONTAINING
70,000 LB 12/20 MESH SAND, MAXP 3650", MINP 3400", AR 29BPM, AP 3500" ISTP 1640" 15M 1450"
TTH W/ 6 1/4" BIT, DC'S, 2 7/8" WS CLEAN OUT SAND TO TD (3710'), TOH LAYING DOWN WS
TTH W/ TGG, RODS, AND PUMP (SN @ 3535') PLACE ON PRODUCTION
ON 24 HR POTENTIAL TEST ENDING 11:00AM 6-5-89 46 BNO 120 BFW 123 MCFD
FROM LANGLEY MATRIX SEVEN RIVERS QUEEN OPEN HOLE INTERVAL FROM 3388' TO 3710'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

AREA SUPERINTENDENT

JUN 7 1989

SIGNATURE

TYPE OR PRINT NAME

K.L. Johnson

TITLE

DATE

TELEPHONE NO.

314-2585

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

JUN 9 1989

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY