


N

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico



WELL RECORD

DUPLICATE

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Skelly Oil Co.

Tulsa, Oklahoma

Company or Operator

Address

H. O. Sims

Well No.

9

in 6NW SW

of Sec.

34-22-37

T.

Lease

R. _____, N. M. P. M. _____, Skelly, Field, Lea County.

Well is 3300 feet south of the North line and 4000 feet west of the East line of Sec. 34 -

If State land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is Hugh O. Sims, Address Eunice, New Mexico

If Government land the permittee is _____, Address _____

The Lessee is Skelly Oil Co., Address Tulsa, Oklahoma

Drilling commenced Mar. 10, 1940 19 _____ Drilling was completed April 27, 1940

Name of drilling contractor Sahara Oil Co., Address Monahans, Texas

Elevation above sea level at top of casing 3330 feet.

The information given is to be kept confidential until _____ 19 _____

OIL SANDS OR ZONES

No. 1, from 3537' to 3638' No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
16"	30#	8	LN	78' 10"					
15"	30#	8	LN	43' 10"					
10-5/8"	40#	8	LN	72' 10"					
8-5/8"	32#	8	LN	1143' 0"					
7"	20#	8	SS	3420' 0"					
2"	4.7#	8	SS	3540' 11"					

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12 1/2"	16"	87'	100	Halliburton - Cement circulated back to collar.		
8"	7"	3400'	250	Halliburton		
Also - 8-5/8" 8" casing was landed at 1158' and was not pulled.						

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment _____

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet

Cable tools were used from Top feet to 3670' feet, and from _____ feet to _____ feet

PRODUCTION

Put to producing April 23, 1940

The production of the first 24 hours was 126 barrels of fluid of which 100 % was oil; _____ %

emulsion; _____ % water; and _____ % sediment. Gravity, Be _____

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Lee Coleman

Driller

Melvin Lard

Driller

W. H. Lunivan

Driller

Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 7 _____ Hobbs, New Mexico June 5, 1940

day of June 1940

Notary Public

My Commission expires Dec. 10, 1940

Name _____
Position _____
Representing _____
Company or Operator _____
Address _____ Hobbs, New Mexico

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
100	20	20	Soil
20	80	60	Sand
80	87	7	Red bed
87	120	33	Red shale
120	130	10	Sandy shale
130	300	170	Red sandy shale
300	325	25	Gray shale
325	435	110	Red bed & red rock
435	505	70	Shale
505	670	165	Red bed
670	735	65	Shale, sandy gray
735	745	10	Sand
745	835	90	Gray shale
835	850	15	Brown shale
850	895	45	Red rock & shale
895	1150	255	Red rock & red bed
1150	1240	90	Anhydrite
1240	1535	295	Anhydrite & salt
1535	1600	65	Salt & red bed
1600	1730	130	Salt
1730	1780	50	Salt & red shale
1780	1800	20	Salt & potash
1800	1930	130	Anhydrite
1930	1975	45	Potash & salt
1975	2030	55	Anhydrite & salt
2030	2425	395	Brown lime
2425	2525	100	Lime & anhydrite
2525	2925	400	Brown lime & anhydrite
2925	2980	55	Brown lime
2980	3010	30	Gray lime
3010	3035	25	Lime & anhydrite
3035	3050	15	Gray lime
3050	3075	25	Lime & anhydrite
3075	3305	230	Gray & brown lime
3305	3320	15	Lime
3320	3405	85	Lime & anhydrite
3405	3409	4	Lime
3409	3485	76	Lime
3485	3510	25	Gray lime & sandy shale
3510	3545	35	Lime
3545	3555	10	Sandy lime
3555	3615	60	Soft sandy lime
3615	3635	20	Hard lime
3635	3655	20	Med. Brown sand & lime
3655	3670	15	Lime