

| | |
|-----------------|--|
| COPIES RECEIVED | |
| DISTRIBUTION | |
| | |
| | |
| OFFICE | |
| FOR | |

50-028-10985

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEPLEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.

WELL ☐ GAS WELL ☐ OTHER- ☒ Plugged and Abandoned

1. Name of Operator

Skelly Oil Company

2. Address of Operator

P. O. Box 1351, Midland, Texas 79701

4. Location of Well

UNIT LETTER M 660 FEET FROM THE South LINE AND 510 FEET FROM
THE West LINE, SECTION 34 TOWNSHIP 22S RANGE 37E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name
H. O. Sims

9. Well No.
16

10. Field and Pool, or Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)
3335' DF

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☐
CASING TEST AND CEMENT JOB ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ☒ Replugged and abandoned

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well was plugged and abandoned September 16, 1967. Due to water flows into non-unitized intervals, the New Mexico Oil Conservation Commission requested that this well be replugged to meet current standards.

- 1) Moved in workover rig February 25, 1975.
- 2) Drilled out cement and cleaned out to 3507'.
- 3) Spotted 250 sacks cement plug 2350-3507'.
- 4) Spotted 300 gals. 15% acid 1000-1103'.
- 5) Perforated 8-5/8" OD casing at 1096' with four 0.38" diameter holes.
- 6) Set cement retainer at 1016' and cement squeeze 8-5/8" OD casing perfs. with 190 sacks Class "C" cement 2% CaCl.
- 7) Spotted 10 sacks cement plug 984-1016'.
- 8) Spotted 20 sacks cement plug. Surface to 50'.
- 9) Install dry hole marker.

Well plugged and abandoned March 2, 1975.

NOTE: All intervals not cemented were filled with 10.2# mud.

18. I hereby certify that the information above is true and complete to the best of my knowledge.

(Signed) D. R. Crow

D. R. Crow

Lead Clerk

3-12-75

SIGNED

TITLE

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Geologist

APR 23 1975

RECEIVED

MAR 1 1976

OIL CONSERVATION COMM.
LONGO, IL. IL.