

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

HOBBBS OFFICE D. C. C.
NEW MEXICO OIL CONSERVATION COMMISSION

SEP 6 11 45 AM '67

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. ..
7. Unit Agreement Name ..
8. Farm or Lease Name H. O. Sims
9. Well No. 16
10. Field and Pool, or Wildcat ..
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Water Well
2. Name of Operator Shelly Oil Company
3. Address of Operator Box 730 - Hobbs, New Mexico
4. Location of Well UNIT LETTER M 660 FEET FROM THE South LINE AND 510 FEET FROM THE West LINE, SECTION 24 TOWNSHIP 22-S RANGE 37-E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 3335' DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We now plan to plug and abandon this Water Supply Well in the following manner:

1. Move in and rig up Pulling Unit.

2. Pull rods and casing pump.

3. Run 2-3/8" O.D. Tubing Work String to 3890'.

4. Perforate 5-1/2" O.D. casing left in hole with thru-tubing gun from 3890-3900' with 4 shots per foot.

5. Spot cement plugs at the following depths:

3900-3825' - 50 sacks
3700-3350' - 300 sacks
2820-2760' - 20 sacks

6. Spot 10 sack cement plug at surface inside of 8-5/8" O.D. casing and install dry hole marker.

7. All intervals not cemented will be filled with heavy mud laden fluid.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____

TITLE **District Superintendent**

DATE **September 5, 1967**

APPROVED BY _____

TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

5 1/2" Ported
3557' - 5774

Squeezed