NEW MEXICO OIL CONSERVATION COMMISSION SANTA FE, NEW MEXICO MISCELLANEOUS NOTICES

begin. A copy will be returned to the sender of	vation Common which wi	mission or its proper agent before the work special be given the approval, with any insulication be the plan submitted. The plan as approved should be additional instructions in the Rules and Regul	Totlowed.
the Commission.		ice by checking below:	
NOTICE OF INTENTION TO TEST CASING SHUT-OFF		NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE PLANS	3	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR WELL	X	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN WELL		10 LL 2 TE - 42 LL	
	idland,	, Texas September 21, 19 Place Date	149
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.			
Gentlemen:		To Taxas	
Following is a notice of intention to do certain	work as de	scribed below at the Well No. 2 in S	SEt SEt
Company or Operator	Lease		
of Sec. 16 , T. 23 S , R. 36	<u>5 E</u> , N	. M. P. M., Cooper Jal	Field.
Lea Cour			
		POSED PLAN OF WORK	
FOLLOW INSTRUCTIONS IN THE		ND REGULATIONS OF THE COMMISSION	
	TD: 30 PBTD:	669-Lime	
	LDID:	J410	
7" Casing comented at 3500 with Perforations in 7" casing: 3 3 3 3 3	1211-218	sacks. 0300 holes, 3195-320560 ho 5120 holes, 3240-3265150 holes, 3315-3345180 ho	oles, holes, oles.
For last remedial work see C			
harman LEO MOR of Con Prod	ログせきんれ	bbl. cil and 660 bbls. water for April 1949 was 107 bbls. oduction varied from 40 to 60	O T T 9 T T T
In June 1949, a Dowell Spinn	er Surv	ey was run on well which indi	cated a
Approved		The Texas Company (Co	nt'd en back)
		By May sur	
		Position List. Supt. Send Communications regarding well	to
oil conservation commission,	,	Name The Pexas Company	
By Roy yorurally.		Address Ecx 1270	
Title	PROTOR	Midland, Texas	· · · · · · · · · · · · · · · · · · ·

large amount of water was coming from section below 3340.

In an effort to reduce the large secunt of water produced to the extent that that well can become a connercial producer, we desire to shut off lower section of casing by slugging back well with pesgravel to appreximately 3350 and with hydromite to appreximately 3270. Test well after alugheck,