

DUPLICATE

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

RECEIVED
JUN 24 1947

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

June 23, 1947

Midland, Texas

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

The Texas Company's State of New Mexico "B" Well No. 2 in the
Company or Operator Lease
SE/4 SE/4 of Sec. 16, T. 23-S, R. 36-E, N. M. P. M.,
Cooper-Jal Field, Lea County.

The dates of this work were as follows: (See below)

Notice of intention to do the work was ~~received~~ submitted on Form C-102 on December 18, 1946
and approval of the proposed plan was ~~received~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Total Depth 3700'---5-9-44 Plugged back to 3675'---Before workover- casing pump removed and steel line measurement showed Total Depth to be 3646'.

Permeability and "Dowell Spinner" Surveys indicated water entry 3490-3492' (ground measurement) or 2' below casing seat. Hole was filled with pea gravel to 3519', 2 sacks Cal-seal to 3508'. Set Baker retrievable retainer at 3465' and squeezed casing seat with 100 sacks cement. Drilled plug and cleaned out to 3646'. On 12-18-46 acidized with 2000 gallons (Western) from 3510-3633', On 1-22-47 pumped 7 barrels oil & 757 barrels water.

Witnessed by _____ Name _____ Company _____ Title _____

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

23rd day of June, 1947

Name E. HollimanPosition District SuperintendentRepresenting The Texas Company
Company or Operator

My commission expires June 1, 1949

Address Box 1270, Midland, Texas.

Remarks:

RECEIVED
JUN 24 1947
Date

Roy Yarbrough
Name
Oil & Gas Inspector