

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S	
LAND OFFICE	
TRANSPORTER	OIL GAS
PRODUCTION OFFICE	
OPERATOR	

Offset Oper.
 Cont: Ital Oil Co.
 TPC&O Co.
 Texas Co.

(Form C-102)
 (Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION
 Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	XX	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
 SANTA FE, NEW MEXICO

Hobbs, New Mexico,
 (Place)

Feb. 5, 1962
 (Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Sinclair Oil & Gas Company State 157"FB" Well No. 1 in A
 (Company or Operator) Lease (Unit)
 NE 1/4 NE 1/4 of Sec. 17, T. 23S, R. 36E, NMPM, Jalmat Gas Pool Pool
 (40-acre Subdivision)
 Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 3600FB

Propose to Plug & Abandon account production from present producing zones has exhausted.

Well Completed as: 325' of 16"OD Casing Cemented w/ 200 Sks. Cement Circulated

1448' of 10 3/4" Casing Cemented w/ 100 Sks.

3668' of 7"OD Casing cemented w/ 200 Sks.

Perforations 3430 to 3470

Propose to plug in following manner:

Set 50 Sk. Cement plug f/ 3600 to 3400' & Fill hole w/ heavy mud

Shoot off 7"OD Casing @ Approx. 2000' - Set 25 Sk. Cement plug in top of 7" stub

Top Salt @ 1539' - Set 25 Sk. Cement plug in top Salt

Shoot off 10 3/4"OD Casing @ Approx. 800' and set 15 Sk. Cement plug in top of 10 3/4"OD stub,

Set 15 Sk. cement plug in bottom of 16"OD Casing.

Set regulation "Marker" in top of 16"OD Casing & bottom of cellar in 10 Sk. cement plug,

Fill cellar & Level location.

Pull all casing shot off

Approved....., 19.....
 Except as follows:

Sinclair Oil & Gas Company
 Company or Operator

By.....

Position..... Dist. Supt.
 Send Communications regarding well to:

Approved
 OIL CONSERVATION COMMISSION

By.....

Name..... W. F. Burns,

Title.....

Address..... 520 E. Broadway, Hobbs, N.M.