

(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office Las Cruces  
Lease No. LC 030557 a  
Unit 1000

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Farney 3-17

January 23, 1958

Well No. 2 is located 600 ft. from N line and 1650 ft. from XX line of sec. 17

N 1/4 Sec. 17 23S 36E  
(1/4 Sec. and Sec. No.) (Twp.) (Range)

Jalmat Lea New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is intended to drill this well at the above location to an estimated TD of 3750'. Casing will be cemented in accordance with U.S.G.S. standards and other special requirements will be complied with.

The following casing pattern is planned: 8 5/8" CD set at 350' with 350 sacks, cement to circulate; 5 1/2" CD set at 3750' with 1100 sacks, cement to return to 1600'.

Permission is requested to produce this well upon completion.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Continental Oil Company

Address Box 68

Alamogordo, New Mexico

By [Signature]

Title District Superintendent

Approval is subject to the following:

1. Cement behind the 5" casing must cover the Salt section as determined by temperature survey or the Salt section must be isolated by use of a two-stage cementing process.