Submit 3 Copies To Appropriate District Office	State of New Mexico			Form C-103
District I Energy, Minerals and Natural Resources 1625 N. French Dr., Hobbs, NM 88240			Revised March 25, 1999 WELL API NO.	
District II 1301 W. Grand Avenue, Artesia, NM 88210 OIL CONSERVATION DIVISION		30-025-1211		
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Fr		5. Indicate Type	
District IV	Santa Fe, NM 8	7505	STATE 6. State Oil &	
1220 S. St. Francis Dr., Santa Fe, NM 87505			o. State Oil &	Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other			7. Lease Name of Dollie Balleno	or Unit Agreement Name: ger
2. Name of Operator Chevron USA, Inc.			8. Well No.	
3. Address of Operator 15 Smith Rd. Midland, Tx 79705			9. Pool name or Wildcat	
4. Well Location			Blinebry Bruns	on Drk. ABO
Unit Letter_M 66	0feet from the south	line and 66	0feet fro	m the West line
Section 17	Township 22-S R	ange 38-E	NMPM	County Lea
April 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0. Elevation (Show whether L		(c.)	County 200
11 Check Apr	proprieto Doy to Indicate M	others - CNT /		
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:				
	PLUG AND ABANDON	REMEDIAL WOR		PORT OF: ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DR	LLING OPNS.	PLUG AND
	MULTIPLE COMPLETION	CASING TEST AND CEMENT JOB		
OTHER:		OTHER:		
12. Describe proposed or completed of starting any proposed work). So or recompilation. 1. Set 5 1/2 CIBP @ 5660' sp. 2. Displace hole w/MLF, 9.5# 3. Spot 25sx plug fr/4000' to 34. Cut 5 1/2" csg @ 2950' un 55. Cut 5 1/2" @ 3500' L/D and 55. Cut	oot 25sx plug fr/5660'to5460' Brine w/25# Gel p/BBL 3800' (Queen) able to sgz spot 45sx plug fr/	Completions: Attacl	n wellbore diagram 5436' 5/8 shoe Yates R	of proposed completion
5. Cut 5 1/2" @ 2500' L/D csg 6. Spot 75sx plug fr/1500' to 7. Circ cmt fr/400' to surf w/11 8. Install dry hole marker 10	g spot 75sx plug tr/2550 to 23 I300' (T-salt) Tag @ 1260' I5sx (13 3/8 shoe) Tag @ sul	350' (stub) Tag @	2263'	, 00
	- temperature	l as to plugging ounder bond is retained as comparation is comp	المالية المسادة	
I hereby certify that the information ab	ove is true and complete to the b	est of my knowledg	ge and belief.	
SIGNATURE 1		MANAGER/	SUNSET	DATE 10/7/02
Type or print name Jimmy B	AGLEY		Telepl	none No.915 520-8756
(This space for State use)	,			FEB 1 7 200
APPPROVED BY Conditions of approval, if any	TITLE_			_DATE
GARY VAWINK OF FIELD REPRE	Sentative II/Staff Manac	SER		42
- ·				~\ <i>J</i>