

4-1-56

PACKER LEAKAGE TEST

Operator The Texas Company (Upper Completion) Blinebry (Gas)
Lease A.H. Blinebry (NCT-1) well 1 (Lower Completion) Tubb (Gas)
Location: Unit 0, S 19, T 22-S, R-38-E, Lea County, N. M.

Shut-in at (hour, date)..... 8:00 A.M. 10-30-58 4:45 PM 10-29-58
Pressure stabilized at (hour, date)..... 12:00 (noon) 10-30-58 7:00 PM 10-29-58
Length of time required to stabilize (hours)..... 4 2:25

Flow Test No. 1

Test commenced at (hour, date) 9:55 A.M. 11-3-58 Choke size 32/64
Completion producing tubing (Tubb) Completion shut-in casing (Blinebry)
Upper Completion Lower Completion
Stabilized pressure at beginning of test..... 1510 psi 1920 psi
Maximum pressure during test..... 1510 psi 1920 psi
Minimum pressure during test..... 1510 psi 1750 psi
Pressure at end of test..... 1510 psi 1750 psi
Maximum pressure change during test..... 0 psi 170 psi
Oil flow rate during test: 65 BOPD based on 60 BC in 22.25 hours.
Gas flow rate during test: 2250.7 MCFPD based on 2085 MCF in 22.25 hours.

Mid-Test Shut-In

Shut-in at (hour, date)..... 8:00 A.M. 10-30-58 8:10 AM 11-4-58
Pressure stabilized at (hour, date)..... 12:00 (noon) 10-30-58 7:00 PM 11-4-58
Length of time required to stabilize (hours)..... 4 10.8

Flow Test No. 2

Test commenced at (hour, date) 9:45 AM 11-5-58 Choke size 22/64
Completion producing casing (Blinebry) Completion shut-in tubing (Tubb)
Upper Completion Lower Completion
Stabilized pressure at beginning of test..... 1510 psi 1910 psi
Maximum pressure during test..... 1510 psi 1920 psi
Minimum pressure during test..... 1190 psi 1910 psi
Pressure at end of test..... 1200 psi 1920 psi
Maximum pressure change during test..... 320 psi 10 psi
Oil flow rate during test: 62 BOPD based on 58 BC in 22.5 hours.
Gas flow rate during test: 2157.6 MCFPD based on 2022.4 MCF in 22.5 hours.

Test performed by J. G. Blevins, Jr. Title Petroleum Engineer

Witnessed by _____ Title _____

REMARKS: Notified New Mexico Oil Conservation Commission by letter dated
October 31, 1958, prior to initiating packer leakage test.

NOTE: Recording was made of this test and a graphic depiction of all phases of the test shall be submitted to the Commission.

AFFIDAVIT:

I HEREBY CERTIFY that the foregoing was performed by Oil Conservation Commission of the State of New Mexico and that the same was complied with and carried out in full, and that the facts stated herein are true and correct.

J. G. Blevins, Jr. THE TEXAS COMPANY
(Representative of Operator) (Company Making Test)

SWORN TO AND SUBSCRIBED before me this 11th day of November, 19 58

W. E. Choyle
Notary Public for the County of Midland
Texas

INSTRUCTIONS
(SOUTHEAST NEW MEXICO ONLY)

1. At least 24 hours prior to the commencement of this test, the operator shall notify the District Office of the Oil Conservation Commission in writing of the exact time said test is to be commenced.
2. The packer leakage test shall commence with both sides of the completion shut-in. Both sides of the completion must be shut-in a sufficient length of time to allow for complete stabilization of both wellhead pressures, and for a minimum of 2 hours thereafter- this minimum of 2 hours shut-in must show on the charts of the pressure recorder and also must appear on the data sheet.
3. For Flow Test No. 1, one side of the dual completion shall be produced with the other side shut-in. Such test shall be continued until the flowing wellhead pressure has become stabilized and for a minimum of 2 hours thereafter, and shall be at a rate of flow approximating the normal rate of flow for the zone being produced.
4. Following the completion of flow test No. 1, the well will again be shut-in, and remain so until the wellhead pressures have again become stabilized and for a minimum of 2 hours thereafter.
5. Flow Test No. 2 shall be performed with the previously shut-in side of the dual completion flowing and with the flowing side of the completion used in test number 1 remaining shut-in. This test shall be conducted exactly as outlined under Flow Test No. 1, and must be performed even though no leak was indicated by Flow Test No. 1.
6. All pressures, throughout the entire test, must be continuously measured and recorded with recording pressure gauges.
7. The accuracy of the recording gauges shall be checked at regular intervals throughout the test with a dead weight test gauge, and such readings shall be recorded on the test data sheet provided.
8. For any well on which the wellhead pressures will not stabilize in (24) twenty four hours or less, the minimum producing or shut-in time allowed for stabilization shall be (24) twenty-four hours.
9. This form must be completed and filed in duplicate with the District Office of the Oil Conservation Commission within 15 days following the completion of the testing, and must be accompanied by:
 - a. all of the charts, or copies thereof, used on the pressure recorders during the test.
 - b. the test data-sheet (s), or copies thereof, required under paragraph 7 above.
 - c. a graph depicting the pressures and their changes, for both sides of the completion over the entire test.
10. This packer leakage test shall be performed upon dual completion of any new wells so approved by the Commission. This test shall also be required each year during the annual GOR test for the lowermost oil zone or oil pool so concerned. The Commission may also request packer leakage tests at any time they feel that a new test is desirable.

NEW MEXICO
OIL CONSERVATION COMMISSION

PACKER LEAKAGE TEST

OPERATOR The Texas Company
LEASE NAME A. H. Blinebry (NCT-1) WELL NO. 1
LOCATION Unit O, Sec. 19, T-22-S, R-38-E COUNTY Lea

TEST DATA SHEET

[illegible]







