Form 9-330 LEASE OR PERMIT TO PROSPECT UNITED STATES X DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY LOG OF OIL OR GAS WELL LOCATE WELL CORRECTLY CompanyTeXACO IccAddress P.C. Sur 720 - Houbs, New MexicoLessor or Tract A. H. Hlinency SCT-1Field DrinkardState State State Location 1900 ft. $\left\{ \begin{array}{c} N \\ S \end{array} \right\}$ of $\left\{ \begin{array}{c} M \\ W \end{array} \right\}$ of \left\{ \begin{array}{c} M \\ W \end{array} \right\} of $\left\{ \begin{array}{c} M \\ W \end{array} \right\}$ of \left\{ \begin{array}{c} M \\ W \end{array} \right\} o The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records. he for the C. Signed M. . Title-Assistant-District-----Date October 1961 The summary on this page is for the condition of the well at above date. Superintendent OIL OR GAS SANDS OR ZONES (Denote gas by G) See attached sheet No. 1, from No. 4, from to -- to -----No. 5, from to No. 2, from to No. 6, from to No. 3, from to Drilled with rotary tools and warek sands stud. No. 1, from to No. 3, from to No. 4, from to No. 2, from to CASING RECORD Perforated Weight per foot Cut and pulled from Size casing Threads per inch Kind of shoe Purpose Amount Make From--То--123 Howeo Hone 9-540 -6:00 <u> P 13 R</u> Wono None Surface 23:00 bogo-nowoo--None above Production See 0-99 MUDDING AND CEMENTING RECORD Amount of mud used Mud gravity Method used. Size casing Where set Number sacks of cement -1299 -00 -Howero -64-90-400 Bad Serv PLUGS AND ADAPTERS Adapters-Material Size SHOOTING RECORD Depth shot Depth cleaned out Quantity Date Explosive used Shell used Size -----TOOLS USED Rotary tools were used from ______ feet to ______ feet to ______ feet, and from ______ feet to ______ feet Cable tools were used from ______ feet to ______ feet, and from ______ feet to ______ feet DATES Put to producing _____, 19____ 19-

Budget au No. 42-R355.4. Approva. pires 12-31-60.

FOLD MARK

		101			
The prod	luction for the firs	st 24 hours was 🛒	barrels of fluid of which 100-% was oil;%		
emulsion:% water; and% sediment.			Gravity, °Bé.		
			Gallons gasoline per 1,000 cu. ft. of gas		
		in			
record bio			PLOYEES		
	uman	, Driller	Driller		
	omar.	Driller	, Driller		
به و میر دارد. م		FORMA	TION RECORD		
	1	1			
FROM—	то—	TOTAL FEET	FORMATION		
5 3	0	p. C.	C-24		
ು 26ಂ	201 1122	260 - 197	Caliere Reduka		
1122	1262	1.40	Redrock & Anay		
1262	1299		Phys		
1299	2:75	1276	Auny & Salt		
2.7	3701	1126	Anny & Cyp		
3701	3703	2	Anny & Line		
0700 4071	-671 525	ಕ್ಷಮ ಕ್ಷ	Lime & Achy		
5235	6091	16	Line		
6891	7070	179	Lime & Anny		
7070	7200	130	Lime		
Total De		7200	We are more than the first second		
open nor	○ 67_0 to 72	e up	Formation Tops Top of Anhy - 12:2'		
All meas	urements fra	om rotary	Top of Salt - $1421'$		
		ground level	Btm of Salt - 2315'		
• • • •			Top of Yates - 2600'		
	No. 7-11		Top of San Andres - 40201		
÷ş 🚥	USGS		Top of Glorieta - 5163'		

_163*

6417'

55901

6137'

18-48094-4

Top of Drinkard -

Top of Blinebry -

1999 - 1999 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 - 1996 -

Top of Tubbs -

(OVER)

金融合 新田市

1 - NMOCC

1 - File

6-304

1 - Field

1 - Division

4

FROM	то—	TOTAL FEET		FORMAT	TION
			Depth 269 529 391 1281 1760 2004 2367 3754 4055 4208 4837 5147 5457 5753 5920 6478 6756 7200	Deviation	Record Degrees Off 1/2 3/4 1 3/4 1 3/4 1 3/4 1 3/4 1 3/4 1 1/2 1/2 1/2 1 2 2
••••••••••••••••••••••••••••••••••••••					
	lun ^{zen} Sichner <u>mann</u> en	d Sayest 1. (22)		1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	unan an an an an an an an an an Marting ⊐unan an anna an Annar gallan an an
	· · · · · · ·	in the sub- Contract	a da se de la composición. E		· · · · · · · · · · · · · · · · · · ·
· · · · · · · · ·	···· ···				
			en an an an an Na ann an an		
	en en la strander Hate. N				
					n an ann an Air an A Air ann an Air
		and the second second		e and a second sec	· · · · · · · · · ·
	e Replikeen jan Staat	人名法阿尔克 医白白白白 计算法		e nastra ager	n - Na - San
			g divinis - Ma Georgia		<u>.</u>
Constant South and the second		ti i ti tate po c		°	en de la complete
	in the point	(1,1) $(1,1)$		the Charles and	
			70 A 74200 -		
F		1			
-· .	· · ·				
е. С. 1		na Nganagan jab	an a	n Server	in franciscus de la composition de la c
	a a sa tina a sa tina mangala.		en de la composition 11 de la composition d'Altri	a da <u>argan</u> a ang sa	
11) : 11 (Alexandria)	an an Arian			· · · · · ·	
in the second second	na na serie de la companya de la company				en jarren er en er en er
			7 ^{- 1} 12.1.17.		
	:	and the second sec			and a second
-	• • •	and the second sec			· · · · · · · ·
					in the second
lan ar an ta			(*~.)	ι. - Δ	
	¢		a a sa a	an a	n for an an ann an an an Array an Array
		· · · · · · · ·			

FORMATION RECORD—Continued

It is of the greatest importance to have a complete history of the well. Please state in detail the dates of redrilling, together with the reasons for the work and its results. If there were any changes made in the casing, state fully, and if any casing was "sidetracked" or left in the well, give its size and location. If the well has been dynamited, give date, size, position, and number of shots. If plugs or bridges were put in to test for water, state kind of material used, position, and results of pumping or bailing.

 $W^{\rm res} = \sigma(m, r)$



D.S. LAND GEORGE

Зары ускела сторо со со с Темаро ускела сторо сторо с

16-43094-2 U. S. GOVERNMENT PRINTING OFFICE

Letter Constant

DEPARTMENT OF THE OTTERIOS

GEORGOIOST REEACC

한 것을 모음 것 것을 것을 가장 것 것을 수 없는 것을

			 Complete the second seco	
1	an 1995) An an Antonio	· · ·	· · · · · · · · · · · · · · · · · · ·	•• •
land the second second			1. j. k. a. e. 284 - 1. a.	
and a second	$\sum_{i=1}^{n} e_{i} = \sum_{i=1}^{n} e_{i} e_{i} e_{i} e_{i} + \sum_{i=1}^{n} e_{i} + \sum_{i=1}^{n} e_{i} e_{i} + \sum_{i=1}^{n} e_{i} e_{i} + \sum_{i=1}^{n} e_{i} e_{i} + \sum_{i=1}^{n} e_{i$			
$(\mathcal{F}^{(1)})^{(1)} (\mathcal{F}^{(1)})^{(1)} (\mathcal{F}^{(1)}$		· • •		
the second s	······································			· • • · · ·
	· · · · · · · · · ·			

	INCLUSION COLUMN	the contact ways	
$\frac{1}{2} \left(\frac{1}{2} \frac{\mathbf{x}}{\mathbf{x}} + \frac{2\mathbf{x}}{2} \frac{\mathbf{x}}{2} - \frac{2\mathbf{x}}{2} \frac{\mathbf{x}}{2} - \frac{2\mathbf{x}}{2} \frac{\mathbf{x}}{2} - \frac{2\mathbf{x}}{2} - $	$\frac{1}{2} = \frac{1}{2} \left(\frac{1}{2} + \frac{1}{2} \right) \left(\frac{1}{2} + \frac{1}{2} + \frac{1}{2} + \frac{1}{2} \right) \left(\frac{1}{2} + \frac{1}{2} + \frac{1}{2} + \frac{1}{2} \right) \left(\frac{1}{2} + \frac{1}{2} + \frac{1}{2} + \frac{1}{2} + \frac{1}{2} \right) \left(\frac{1}{2} + \frac{1}{2}$	the state of the second	and the second second
	and the second	n ∦ Statistic	and the second
	and the second	g and start	eren en e
	the state of the s	ando jana na sila	

See attached sheet

WELL RECORD A. H. BLINEBRY NCT-1 WELL NO. 12

Spudded 12 1/2" hole 2:00 a.m. August 3, 1961. Ran 1283' of 9 5/8" O.D. casing and cemented at 1299' with 500 sx Reg, 4% Gel and 200 sx NEAT. Cement circulated. Plug at 1267'. Tested 9 5/8" O.D. casing before and after drilling cement plug for 30 minutes with 1000 PSI. Tested O.K. Job complete 8:00 a.m. August 6, 1961.

- DST #1 5135' to 5185' tool open 2 hrs. w/ fair blow increasing to strong blow in 1 hr. No fluid to surface. Rec 260' 0 & GCM & 250' mud cut w/sul water. HI & HO 2735# ISIP 713# IFP 100# FFP 234# FSIP 368# Complete 9:30 a.m. 8-18-61.
- DST #2 5590' to 5740' tool open 1 hr with weak blow thru out. No fluid to surface. Rec 500' DM. ISIP 220# IFP 122# FFP 155# FSIP 197# HI 3018# HO 3004# Complete 2:00 p.m. 8-21-61. DST #3 6170' to 6300' tool open 2 hrs Gts in 7 minutes Rec 1350'
- DST #3 6170' to 6300' tool open 2 hrs Gts in 7 minutes Rec 1350' 0 & GCM. ISIP 1350# IFP 350# FFP 385# FSIP 1665# HI & HO 3485# Complete 9:00 a.m. 8-26-61.

Ran 6338' of 7" O.D. casing and cemented at 6850' with 400 sx Incor. Plug at 6828'. Tested 7" O.D. casing before and after drilling cement plug for 30 minutes 1000 PSI. Tested O.K. Ran electric logs September 6, 1961.

DRINKARD ZONE: Acidize open hole 6850' to 7200' with 9000 gals LST NEA.

BLINEBRY ZONE:

Perforate 7" O.D. casing 5591' to 5597', 5602' to 5617', 5622' to 5631', 5634' to 5649', and 5664' to 5691' with 1 shot per 3'. Acidize with 5000 gals LST NEA in 2 stages with 250# Napthalene between stages. Frac with 20,000 gals ref oil and 30,000# sand.

PADDOCK ZONE:

Perforate 7" O.D. casing 5168' to 5174' with 1 jet shot per 3'. Acidize with 250 gals LST NEA. Re-acidize with 1500 gals LST NEA. Squeeze with 75 sx Incor NEAT with LWL and retarder additives. Stage 2 the same vol and type cement. Stage 3 with 75 sx Incor NEAT with 70# LWL and 14# retarder additives. Perforate 7" casing with 2 jet shots per ft. 5168' to 5174'. Acidize with 500 gals LST NEA. Swab dry. Re-acidize with 1500 gals LST NEA. Swab dry. Squeeze with 150 sx Incor NEAT.

DRINKARD ZONE TEST: On 16 hr Potential Test ending 11:00 p.m. October 1, 1961 well flowed thru 14/64" choke 120 BO and no water. GOR - 900 Gravity - 33.0 Top of Pay - 6850' Btm of Pay - 7200' USGS Date - September 1, 1961 TEXACO Inc. Date - October 1, 1961.

BLINEBRY ZONE TEST: On 4 hr Potential Test ending 5:00 p.m. September 29, 1961 well flowed thru 18/64" choke 88 BO and no water. GOR - 2382 Gravity - 41.0 Top of Pay - 5591' Btm of Pay - 5691' USGS Date - September 1, 1961 TEXACO Inc. Date - September 29, 1961