

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division  
P.O. Box 1980  
Hobbs, NM 88241

FORM APPROVED  
Budget Bureau No. 100M-0115  
Expires: September 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Texaco E&P Inc.

3. Address and Telephone No.

P.O. Box 3109 Midland, Texas 79702 (915) 688-4492

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
660 FSL, 1980 FEL Sec 20 T22S R38E Unit Letter O

5. Lease Designation and Serial No.

41655

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

A.H. Blinebry Fed NCT-1#

9. API Well No.

30-025-12141

10. Field and Pool, or Exploratory Area  
Brunson Drinkard

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. Notify BLM of intent to plug
2. MIRU E string NU BOP
3. Set 2 7/8 CIBP@6850 w/20' cement
4. RIH circulate hole w/9.5# mud
5. 10 sx cement 6130-6030
6. 10 sx cement 5800-5700 WOC/tag (holes 5800-5700)
7. 10 sx cement 5600-5500
8. 10 sx cement 5200-5100
9. 10 sx cement 2600-2500
10. POH RU on N string NU BOP
11. Set CIBP@ 5630 w/20' cement
12. RIH circulate hole w/9.8# mud
13. 10 sx cement 5200-5100
14. 10 sx cement 2600-2500 (Yates/shoe) WOC/tag
15. POH RU on W string
16. RIH circulate Hole w/9.8# mud @ 5343
17. 10 sx cement 5200-5100
18. 10 sx cement 2600-2500 (yates/shoe) WOC/tag
19. Cut and pull 2 7/8 csg from 2200±
20. 35 sx cement 2200-2100
21. 35 sx cement 1400-1300
22. 10 sx cement 30'-surface
23. Cut wellhead install dry hole marker
24. RDMO clean location

N-Blinebry  
W-Glorietta  
E-Drinker

SEE ATTACHED FOR  
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct

Signed David W. Skop

Title Reservoir Engineer

Date 4/28/98

(This space for Federal or State office use)

(ORIG. SGD.) GARY GOURLEY

PETROLEUM ENGINEER

Approved by  
Conditions of approval, if any:

Title

Date MAY 14 1998

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as in any matter within its jurisdiction.

\*See instruction on Reverse Side