Form 9-331 a (March 1942)

(SUBMIT IN TRIPLICATE)

UNITED STATES

DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Land Office	Las	Cruces
Lease No	0321	.04
Unit		

SUNDRY NOTICES AND REPORTS ON WELLS

			•
NOTICE OF INTENTION TO DRILL	subs	SEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE P	1 : 11	SEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATE	t 11	SEQUENT REPORT OF ALTERING CASING	1 1
NOTICE OF INTENTION TO RE-DRILL		SEQUENT REPORT OF REDRILLING OR REPAIR	ايسا
NOTICE OF INTENTION TO SHOOT OR	- 1	SEQUENT REPORT OF ABANDONMENT	- <u>X</u>
NOTICE OF INTENTION TO PULL OR A		PLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON	WELL		
(INDICAT	E ABOVE BY CHECK MARK NATURE OF	· · · · · · · · · · · · · · · · · · ·	
A. R. Blinebry	<u> Midi</u>	end, Texas, September	18 , 19.46
Vell No is loc	ated 660 ft. from S	ine and 1980 ft. from line	of sec. 20
(4 Sec. and Sec. No.)	22-9 38-5	(Meridian)	
(¼ Sec. and Sec. No.)	(Twp.) (Range)	(Meridian)	*
Drinkard		New Mex	100
(Field)	(County or Subdivision	on) (State or Territo	ry)
he elevation of the derrick	floor above sea level is 3	397 ft.	
	DETAILS OF		
tate names of and expected depths to	objective sands; show sizes, weights, ing points, and all other import	and lengths of proposed casings; indicate mu tant proposed work)	dding jobs, cement-
		377' - Granitie Rock	
13-3/8" cesing cem at 2633' with 1650	ented at 274' with sacks.	h 300 sacks. 9-5/8" (asing cemer
plugged end sbander leavy mud and cemer 1550; 12 sacks, 7: 1520; 20 sacks, 6: 1240; 20 sacks, 6:	nder date of June ned in the followint plugs were spoi 210'-7150'; 20 sec 270'-6180'; 20 sec	otion to abandon well' 15, 1946, this well! ing menner: Hole was tted as follows: 10 s oks, 7000'-6940': 20 s oks, 5550'-5490': 20 s oks, 4310'-4250': 20 s oks, 4310'-4250': 20 s oks, 4310'-4250': 20 s oks, 4310'-4250': 20 s	has been filled with sacks, 7600' sacks, 6580'
ompany THE TEXAS CO			
ddress Box 1270			
Midland, Ter	[A.S	B. Ollo CH	ann
		Title Drlg. & Prod. F	oremen

2680'; lt sacks, 1450'-1420'. The required 4" pipe marker was comented in the top of the hole with 20 sacks of cement, and ell work was sempleted fune 17, 1946, and the hose fon is now cleaned up and ready for inspection.

به کحر