

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate  
(Other instructions  
reverse side)

Form approved  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> <u>S.W.D. WELL</u>		5. LEASE DESIGNATION AND SERIAL NO. <u>LC-032104</u>
2. NAME OF OPERATOR <u>TEXACO INC</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR <u>P.O. BOX 728, HOBBS, NEW MEXICO 88240</u>		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface <u>UNIT LETTER L, 1980' FSL &amp; 330' FWL</u>		8. FARM OR LEASE NAME <u>A.H. BLINEBRY FED. NCT-1</u>
14. PERMIT NO. <u>30-025-12144</u>		9. WELL NO. <u>11</u>
15. ELEVATIONS (Show whether DF, RT, OR, etc.) <u>3386 D.F.</u>		10. FIELD AND POOL, OR WILDCAT <u>SAN ANDRES</u>
		11. SEC., T., R., OR BLK. AND SURVEY OR AREA <u>SECT 28, T-22S, R-38E</u>
		12. COUNTY OR PARISH <u>LEA</u>
		13. STATE <u>NEW MEXICO</u>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
(Other) ☐

PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
ABANDON\* ☐  
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐  
FRACTURE TREATMENT ☒  
SHOOTING OR ACIDIZING ☒  
(Other) ☐

REPAIRING WELL ☐  
ALTERING CASING ☐  
ABANDONMENT\* ☐

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

JUNE 16, 1988 MIRU. RELEASE PKR AND POH w/ INJECTION TBG. TIHW/6' 1/8" BIT. c/o WELL TO PBTD 4800'. TOH.  
RIG-UP WIRELINE. PERFORATE SAN ANDRES POOL AT 4387'-93', 4404'-21', 37'-46', 4507'-12', 21'-27', AND 4664'-75', 2 SPF, 60 FT, 120 SHOTS. RIG DOWN WIRELINE.  
TIHW/7" PKR. ACIDIZE SAN ANDRES PERFORATIONS (4387'-4675') w/ 8,000 GALS 15% NEPE HCLACID. S.I.-12 HRS. FLOWBACK 2 HRS. RECOVERED 80 BLW.  
FRACTURE STIMULATE SAN ANDRES PERFORATIONS (4387'-4675') w/ 35,600 GALS VERSAGEL 1400 CONTAINING 1 1/2 PPG TO 6 PPG 20/40 SAND (75,000 LBS) S.I.- OVERNIGHT.  
5. TOH w/ PKR. TIHW/6' 1/8" BIT. c/o WELL TO PBTD 4800'. TOH.  
TIHW/ INJECTION PKR. SET PKR @ 4330'.  
INJECTING 240 BWPD @ 1210 PSI.  
Complete effective 7-6-88.

RECEIVED  
JUL 11 9 27 AM '88  
CARLSBAD AREA OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED Kent L. Johnson TITLE AREA Supt DATE 7/8/88

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

ACCEPTED FOR RECORD  
John W. Chester  
JUL 20 1988

\*See Instructions on Reverse Side