

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032104

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

A.H. Blinbry Fed NCT-2

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Blinbry & Drinkard11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec 29, T22S, R38E Unit Ltr**

12. COUNTY OR PARISH

Lea

13. STATE

NM1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

Texaco Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728 Hobbs, NM 882404. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface**660' FSL & 1980' FWL of Sec 29, T22S, R38E, Unit Letter N**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3407' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

1. Pull tbg
2. Perf 7" cag w/1 JSPI @ 5617, 48, 60, 70, 90, 96, 5720, 36, 54, 66.
3. Ran RBP & pkr. Set RBP @ 5853 & pkr @ 5510.
4. Acidized perfs 5617-5766 w/2000 gals 15% NEA.
5. Reset pkr @ 5510.
6. Fraced perfs 5617-5766 w/7000 gals gel wtr & 4500# 20/40 sand. C/O sand.
7. Fraced perfs 5617-5766 w/2000 gals gel pad followed w/2100 gals wide frac containing 1# p/gal of 20/40 sand. Followed up w/8200 gals wide frac w/2# p/gal of 20/40 sand followed w/2500 gals wide frac w/2 1/2# p/gal of 20/40 sand.
8. Released pkr.
9. Circulated ad 5639-5853'.
10. Pld RBP.
11. Ran tbg to 7308'. Ran rds & pump.
12. Tested and place on production w/Blinbry & Drinkard downhole commingled.
13. On 24 hr test 11-13-74, pumped 30 BMO, 3 BSW, Gravity 39°, GOR 2500.

Approved by **MOCC** Order No. **DNC-150**

18. I hereby certify that the foregoing is true and correct

SIGNED *J. Schuff*TITLE **Asst. Dist. Supt.**DATE **11-15-74**

(This space for Federal or State office use)


APPROVED BY _____

CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

*See Instructions on Reverse Side



Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-665229

847 - 485

RECEIVED
JUL 1 1964
U.S. GOVERNMENT PRINTING OFFICE
WASHINGTON, D.C.