NO. OF COPICS PECCEIVED				Form C-10)3	
D'STRIBUTION				Supersede	Supersedex Old	
SANTA FE	- NEW ME	NEW MEXICO OIL CONSERVATION COMMISSION		C-102 and Effective		
FILE		AICO OIL COILS	ERTATION COMMISSION			
	-			Sa. Indicate 1	Ype of Leave	
U.5.G.S.	-			Stoto	Fee XX	
LAND OFFICE				5. State Off &	Gas Lease No.	
OPERATOR						
SUNE (00 NOT USE THIS FORM FOR USE WARREIC 1. OIL WELL XX WELL WELL WELL SAS WELL	DRY NOTICES AND PROPERTY OF TO ANTION FOR PERMIT AND POSTERS	REPORTS ON	WELLS CENTRAL DIFFERENT RESERVOIR. CENTRALS SERVERS	7. Unit Agree	ment Nume	
2. Name of Operator					ase Name	
Gulf Oil Corporation						
3, Aldress of Operator						
Box 670, Hobbs, New Mexico 88240						
4. Lecution of Well					Pool, or Wilded	
· • · · ·	1000	North	660	Monta Cr	anita Wash	
UNIT LETTER H	1900 FEET FROM	THE North	LINE AND 660 F	CET TROM WAILE GE	anite Wash	
THE East LINE, SECTION 30 TOWNSHIP 22-S RANGE 38-E NMPM.						
THEEastLINE, SEC	TIOH TO	OWNSHIP ZZ-S	RANGE 38-E	NMPM. (\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
ما المام					777/7/7/7/7//	
	15, Elevet	ton (Show whether l		. 12. County		
		337	3' GL	Lea	<u> </u>	
16. Check	Appropriate Box	To Indicate N	ature of Notice, Report	t or Other Data		
	INTENTION TO:	1		QUENT REPORT O	F:	
11011011 3.	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			•		
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER 17. Describe Proposed of Completed (work) SEE RULE 1103.	CHANG	E PLANS	REMEDIAL WORK COMMENCE DRILLING OPHS. CASING TEST AND CEMENT JOB OTHER Abandoned F and completed in ils, and give pertinent dates, i	Blinebry, drille	ash	
7540' TD, 7492' PB. Pulled producing of Class C containin hours. Tested squee at 6952'. Drilled 6 K-55 LT&C liner and containing 1.75% CFR circulated to PB at Wash zone in 4-1/2" packer on wire line 1200 gallons of 15% gel kerosene contain well up. Pulled tr Placed well on produ	g .5% CFR-2. M zed perforation -1/4" hole to t set at 7539' wi -2. Cement cir 7492'. Tested liner with 4, 1 and set at 7330 NE acid and fra ing 1 to 2# SPG eating equipmen	aximum press with 1,000 otal depth a th top at 66 culated. We liner with 4/2" JHPF at Ran treat with 4,000 AIR 13 BP	#, 30 minutes, OK. t 7540'. Ran 20 jo 48'. Cemented with OC 18 hours. Ran b,000#, 30 minutes, 7381-83' and 7419-2 ting equipment and gallons of gel ker M. ISIP 2500#, aft	sed out 28 sacks Cleaned out to pints, 891' of 4 150 sacks of Coit and drilled OK. Perforated 21'. Ran Baker treated new per cosene and 10,00 ter 15 minutes 2	. WOC 24 total depth -1/2" OD 11.6# lass H cement cement and Wantz Granite Model F-1 forations with O gallons of 100#. Cleaned	
	on above in true and com Orig. Signed by Lerry Sexton		my knowledge and belief, a Engineer		tember 28, 1976	
	Cist 1. Sunv.			3140		

ORDITIONS OF APPROVAL, IF ANY