

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER) to Dually Complete	X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

June 23, 1954
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Vivian

Gulf Oil Corporation
(Company or Operator) Well No. 5 in D
(Unit)
NW 1/4 NW 1/4 of Sec. 30, T. 22-S, R. 38-E, NMPM, Blinebry Gas Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

Propose to Dually Complete as Gas-Gas well in the Blinebry and Tubb Gas Pools as follows:

1. Kill well with mud.
2. Drill out cement and plug at 5690'.
3. Set cast iron bridge plug at 6250'.
4. Perforate casing from 5990-6060' and 6100-6180' with 4, 1/2" Jet Holes per foot.
5. Straddle lower set perforations and treat with 3000 gallons acid.
6. Straddle upper set perforations and treat with 3000 gallons acid.
7. Install Baker Model "D" production packer at 5950'.
8. Run tubing with GOT circulating valve below packer and GOT circulating valve above packer.
9. Swab in upper zone (Blinebry), wash with 500 gallons mud acid if warranted.
10. Close upper circulating valve and open lower valve.
11. Swab in lower zone (Tubb).
12. Produce Tubb Zone thru tubing and Blinebry Zone thru tubing-casing annulus.

Approved....., 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION

By

Title

Gulf Oil Corporation
Company or Operator

By

Position

Area Prod. Supt.
Send Communications regarding well to:

Name

Address

Gulf Oil Corporation

Box 2167, Hobbs, New Mexico