

GULF (CORPORATION - BOARDFORD KH EST# NO. 2  
 SCHEMATIC DIAGRAM OF PROPOSED ABANDONMENT OF DRINKARD ZONE AND DUAL  
 COMPLETION OF BLINEBRY OIL AND TUBB GAS ZONES

7" Csg "H" = 10,500' 2-3/8" Tbg "H" = 9,400' Elev 3357'

13-3/8" OD 48# 8 RT J-55 Csg @ 256'  
 Cmtd w/300 sx. Circ.

256'

9-5/8" OD 36# & 32# 8 RT J-55 & H-10  
 Csg @ 3100'. Cmtd w/1550 sx. TS top @  
 405'

3100'

2-3/8" OD 4.6# Buttress-thd tbg (Oilwell  
 Supply) @ approx 5600'

Parallel tbg anchor @ approx 5600'

Blinebry perms approx 5620-5820'

2-3/8" OD 4.7# J-55 Tbg set @  
 approximately 6100'

Tubb gas perms (FI) 5982-6227'

Perm. prod pkr & receptacle seal assy  
 @ approx 5925'

2-3/8" OD tail pipe w/BPOB @ 7017',  
 filled with sand

50' ext plug on top of sand fill

Maker Model D pkr & receptacle seal  
 assy @ 6770'

67 @ 6770'

67 @ 7000' (closed)

Drinkard perms 6813-7051'

7" OD 23# 8 RT N-80 & J-55 Csg @ 7050'  
 Cmtd w/600 sx. TS Top @ 3465'

TS 3465'