

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY										JUN 11 1962 U. S. GEOLOGICAL SURVEY NEW MEXICO	
1. WELL COMPLETION OR RECOMPLETION REPORT AND LOGS (SUBMIT IN DUPLICATE)										5. LEASE DESIGNATION AND SERIAL 032104	
DESIGNATE TYPE OF COMPLETION NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ OTHER ☐										6. IF INDIAN, ALLOTTEE OR TRIBE NAME None	
2. OPERATOR TEXACO Inc.										7. UNIT AGREEMENT NAME None	
3. ADDRESS P. O. Box 728, Hobbs, New Mexico										8. FARM OR LEASE NAME A.H. Blinebry NOT-3	
4. LOCATION (Report location clearly and in accordance with any State requirements) At surface: This well is located 660' South of North Line and 1980' West of East Line of Sec. 31, Lea County, New Mexico. At top prod. interval reported below At total depth										9. WELL NO. 2	
14. PERMIT NO. - DATE ISSUED - PREVIOUS PERMIT NO. - DATE ISSUED -										12. COUNTY OR PARISH Lea	
15. DATE SPUNDED March 21, 1962										13. STATE N. M.	
16. DATE T.D. REACHED April 15, 1962										17. DATE COMPL. (Ready to Prod.) April 26, 1962	
18. ELEVATIONS (DF, RCB, RT, CR, etc.)* 3353' (D.F.)										19. ELEV. CASINGHEAD FLG. -	
20. TOTAL DEPTH (MD & TVD) 7050'										21. PLUG BACK T.D. (MD & TVD) 7032'	
22. IF MULTIPLE COMPL., HOW MANY? 2 Zones										23. INTERVALS DRILLED BY 7050'	
24. PRODUCING INTERVAL(S), THIS COMPLETION, TOP, BOTTOM, NAME (MD & TVD)* See Attached										25. DATE DIRECTIONAL SURVEY SUBMITTED -	
26. TYPE ELECTRIC AND OTHER LOGS RUN (Circle those filed) See Attached										27. WAS WELL CORKED None	
28. CASING RECORD (Report all strings set in well)											
CASING SIZE	DEPTH SET (MD)	HOLE SIZE	WEIGHT LBS./FT.	PURPOSE	SACKS CEMENT	AMOUNT PULLED					
8-5/8"	1210'	11"	20.00	Surface	600	None					
2-7/8"	7049'	6-1/4"	6.40	Production	*2544	None					
2-7/8"	7049'	6-1/4"	6.40	Production	*2544	None					
							* 2 Strings cemented with 2544 sx.				
29. LINER RECORD										30. TUBING RECORD	
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT *	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)				
None					None						
31. PERFORATION RECORD										32. ACID, SHOT, FRAC., CEMENT SQUEEZER, Etc.	
DEPTH INTERVAL (MD)	HOLES PER FT., SIZE AND TYPE, PURPOSE				AMOUNT AND KIND OF MATERIAL USED		DEPTH INTERVAL (MD)				
See Attached						See Attached					
33. PRODUCTION											
DATE FIRST PRODUCTION		PRODUCING METHOD (Flowing, gas lift, pumping, --- size & type of pump)					WELL STATUS (Prod. or shut-in)				
April 26, 1962		Flowing					Producing				
DATE OF TEST	HOURS TESTED	CHUCK SIZE	PRODUCTION FOR TEST	OIL, Bbls.	GAS, Mcf.	WATER-Bbls.	OIL GRAVITY-APT (Corr.)				
4-29-62	9 Hours	21/64"	→	93	-	31	45				
FLOW. TUBING PRESSURE	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL, Bbls.	GAS, Mcf.	WATER-Bbls.	GAS-OIL RATIO					
600#	-	→	248	-	90	3261					
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be connected later										TEST WITNESSED BY C. F. Jackson	
35. LIST OF ATTACHMENTS Well Record											
36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records											
SIGNED, <i>W.E. Morgan</i>			TITLE Assistant Dist. Supt.				DATE				

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Supplemental instructions by local Federal and/or State officials will govern the use of this form.

If not filled prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and primary logs, and logs of the survey, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be filed in this form, in space 36.

Space 1: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements.

Space 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Spaces 22 and 24: If this well is completed for separate production from more than one zone (multiple-zone completion), so state in space 24, and in space 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the zone reported in space 33. Submit a separate completion report on this form for each interval (zone) to be separately produced.

Space 23: "Backs Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Space 33: Submit a separate completion report on this form for each interval (zone) to be separately produced. (See instruction for spaces 22 and 24 above.)

SUMMARY OF SIGNIFICANT WATER ZONES AND OIL AND GAS ZONES (except as shown on the front hereof)

KIND OF FORMATION (Sandstone, limestone, shale, etc.)	DEPTH TO TOP OF ZONE		DEPTH TO BOTTOM OF ZONE		CONTENTS; PRODUCTIVE RATE, IF KNOWN	NAME	GEOLOGIC MARKERS	
	MEAS. DEPTH	TRUE VERT. DEPTH	MEAS. DEPTH	TRUE VERT. DEPTH			MEAS. DEPTH	DEPTH TO TOP
Caliche	0		231'	231'	Deviation Record	Anhy	1170'	
Red Bed	231'		418'	187'	315' - 1°	Top of Salt	1350'	
Red Bed & Anhy	418'		1050'	632'	819' - 1-1/4	Base of Salt	2300'	
Anhy	1050'		1170'	120'	1918' - 1	Yates	2543'	
Anhy & Salt	1170'		1350'	180'	2816' - 1-1/4	Glorieta	5115'	
Salt	1350'		2295'	945'	3049' - 2°	Blinberry	5490'	
Anhy & Gyp	2295'		2832'	537'	3918' - 1-1/2	Tubbs	6048'	
Anhy & Lime	2832'		3771'	939'	4215' - 1			
Anhy & Gyp	3771'		4104'	333'	4815' - 1-1/2			
Lime	4104'		4894'	790'	5540' - 2°			
Anhy & Lime	4894'		5790'	896'	5980' - 1-3/4			
Lime	5790'		5868'	78'	6245' - 1-1/2			
Lime & Dolomite	5868'		6155'	287'	6781' - 1-1/2			
Lime & Sand	6155'		6680'	525'	6900' - 1-1/2			
Lime	6680'		7050'	370'	7050' - 1-3/4			
TD- 7050'								
PBTD- 7032'								
All Measurements from Rotary Table or 10' above ground level.								